

ASIUKK5

Double-level terminal block
UKJ-4/2-2



UL US CE RoHS

ASIUKKB5

Double-level terminal block
UKJ-4/2-2L



UL US CE RoHS













Dimensions		UL US CE RoHS		UL US CE RoHS	
Width/Thickness/Height	(mm)	56.5 / 6.2 / 61		67.3 / 6.2 / 61	
Screw thread	(mm)	M3		M3	
Tightening torque	(Nm)	0.6-0.8		0.6-0.8	
Stripping length	(mm)	8		8	
Technical data					
Voltage	(V)	500		500	
Max. operating current	(A)	32		32	
Cross section	(mm ²)	4		4	
Connection capacity					
Solid conductors	(mm ²)	0.2-4		0.2-4	
Stranded conductors	(mm ²)	0.2-4		0.2-4	
Terminal block		Type	Order no.	Type	Order no.
		UKJ-4/2-2	011017	UKJ-4/2-2L	011018
BU:Blue		UKJ-4/2-2 (BU)	011111	UKJ-4/2-2L (BU)	011112
Mounting rail					
Can be installed on the rails both and					
		TH35-7.5	102001	TH35-7.5	102001
		TH35-15	102005	TH35-15	102005
		G32-15	102002	G32-15	102002
		G32-18	102003	G32-18	102003
End cover					
For electrical isolation in the end of terminal blocks.					
BU:Blue		UKJ-4/2-2G	012005	UKJ-4/2-2LG	012011
		UKJ-4/2-2G (BU)	012057	UKJ-4/2-2LG (BU)	012061
Spacer plate					
Compensates for level offsets.					
		UKJ-4/2-2ZG	012008	UKJ-4/2-2LZG	012015
		UKJ-4/2-2DG	012013	UKJ-4/2-2LDG	012014
Separating disk					
For separation of neighboring bridges, can be fitted later, no loss of pitch.					
		UKJ-GP	012007	UKJ-GP	012007
Fixed bridge					
For cross connection in the terminal center.					
Screw heads with insulation collar or without.		2-pos.	UFBI 2-6	013072	UFBI 2-6
		3-pos.	UFBI 3-6	013073	UFBI 3-6
		4-pos.	UFBI 4-6	013078	UFBI 4-6
		10-pos.	UFBI 10-6	013002	UFBI 10-6
N:With insulation collar		2-pos.	UFBI 2-6N	013064	UFBI 2-6N
		3-pos.	UFBI 3-6N	013065	UFBI 3-6N
		4-pos.	UFBI 4-6N	013066	UFBI 4-6N
		10-pos.	UFBI 10-6N	013047	UFBI 10-6N
Insertion bridge					
For the connection points with conductors, makes level bridge possible.					
		2-pos.	UEB 2-6	013019	UEB 2-6
		3-pos.	UEB 3-6	013027	UEB 3-6
		10-pos.	UEB 10-6	013013	UEB 10-6
Isolator bridge bar					
A jumping bridge can be made.					
		UISSBI 10-6	013189	UISSBI 10-6	013189
Marker strip					
Horizontally/Vertically					
Blank		UZB 6-10(Blank)	014002	UZB 6-10(Blank)	014002
Can be printed 1-600, or the technical data according to your requirements.		Horizontally	UZB 6-10(Horizontally)	014007	UZB 6-10(Horizontally)
		Vertically	UZB 6-10 (Vertically)	014008	UZB 6-10 (Vertically)
Screwdriver					
		YB 0.6×3.5	304002	YB 0.6×3.5	304002

ASIUK3MVSTB508

Terminal block with needle connection
UKJ-2.5V/5.08



UL us CE RoHS

Dimensions			
Width/Thickness/Height	(mm)	47.8 / 5.08 / 46	
Screw thread	(mm)	M3	
Tightening torque	(Nm)	0.6-0.8	
Stripping length	(mm)	8	
Technical data			
Voltage	(V)	250	
Max. operating current	(A)	12	
Cross section	(mm ²)	4	
Connection capacity			
Solid conductors	(mm ²)	0.2-4	
Stranded conductors	(mm ²)	0.2-2.5	
Terminal block		Type	Order no.
		UKJ-2.5V/5.08	011058
BU:Blue		UKJ-2.5V/5.08 (BU)	011140
Mounting rail			
Can be installed on the rails both 		TH35-7.5	102001
		TH35-15	102005
		G32-15	102002
		G32-18	102003
End cover			
For electrical isolation in the end of terminal blocks. 		UKJ-2.5VG	012034
BU:Blue		UKJ-2.5VG (BU)	012070
Separating disk			
For separation of neighboring bridges, can be fitted later, no loss of pitch. 			
Partition plate			
Covering hood  Provide touch-proof and dust-proof encapsulation.		UKJ-2.5VF	015004
Test plug			
For a test of electrical data with a contact in sockets with a 2.3mm diameter. 		PSB 3	016101
		PS-2.3	Please refer to the attachment for the ordering data.
Fixed bridge			
For cross connection in the terminal center. 		2-pos. UFBI 2-5	013071
Screw heads with insulation collar or without.		3-pos. UFBI 3-5	013070
		4-pos. UFBI 4-5	013140
		10-pos. UFBI 10-5	013001
		2-pos. UFBI 2-5N	013141
		3-pos. UFBI 3-5N	013142
		4-pos. UFBI 4-5N	013143
		10-pos. UFBI 10-5N	013052
N: With insulation collar			
Insertion bridge			
For the connection points with conductors, makes level bridge possible. 		2-pos. UEB 2-5	013018
		3-pos. UEB 3-5	013026
		10-pos.	
Isolator bridge bar			
A jumping bridge can be made. 			
Marker strip			
Horizontally/Vertically Blank 		UZB 5V-10	014019
Can be printed 1-500 or the technical data according to your requirements.		Horizontally 1 2 3 4 5 6 7	UZB 5V-10 (Horizontally)
		Vertically 1 2 3 4 5 6 7	UZB 5V-10 (Vertically)
Switching jumper for 2 terminal blocks 			
Warning label			
			
Screwdriver			
		YB 0.6×3.5	304002