


| Certification | |
|---|--|
|  | |
| Material | |
| Screw | M2.5 Steel, Tin Plated |
| Clamp | Brass, Nickel Plated |
| Housing | Polyamide66, White |
| Electrical | |
| Standard | UL 1059/CSA C22.2 No. 158 |
| Rated Voltage | 600 V |
| Rated Current | 20 A |
| Wire Range | 20-12 AWG |
| Mechanical | |
| Temperature Range | -40°C...+105°C |
| Torque | 0.4N-m (3.6lb-in) |
| Strip Length | 7-8 mm (0.26-0.31") |
| Size | |
| Pitch | 8 mm (.315") |
| Poles | 2P-12P. Additional sizes available on request. |

| Item | No. of Poles | Length (mm) |
|----------------------|--------------|-------------|
| ASIMY8HW+1.2-8.0-2P | 2 | 14.0 |
| ASIMY8HW+1.2-8.0-3P | 3 | 22.0 |
| ASIMY8HW+1.2-8.0-4P | 4 | 30.0 |
| ASIMY8HW+1.2-8.0-5P | 5 | 38.0 |
| ASIMY8HW+1.2-8.0-6P | 6 | 46.0 |
| ASIMY8HW+1.2-8.0-7P | 7 | 54.0 |
| ASIMY8HW+1.2-8.0-8P | 8 | 62.0 |
| ASIMY8HW+1.2-8.0-9P | 9 | 70.0 |
| ASIMY8HW+1.2-8.0-10P | 10 | 78.0 |
| ASIMY8HW+1.2-8.0-11P | 11 | 86.0 |
| ASIMY8HW+1.2-8.0-12P | 12 | 94.0 |