



Certification	
Material	
Screw	M2.5, Steel Zinc Plated
Wire Guard	Copper Alloy, Tin Plated
Cage	Phosphor Bronze, Nickel Plated
Housing	PA66, UL 94V-0, Black
Electrical	
Standard	UL 1059/CSA C22.2 No. 158
Rated Voltage	300 V
Rated Current	12 A
Wire Range	22-14 AWG
Contact Resistance	20mΩ
Insulation Resistance	500MΩ/500 Vdc
Withstand Voltage	2000 Vac/1 Min
Mechanical	
Temperature Range	-40°C...+105°C
Torque	0.4N-m (3.54lb-in)
Strip Length	5-6 mm (0.20-0.24")
Size	
Pitch	5.0 mm (.197")
Poles	2P-16P. Additional sizes available on request.

Item	No. of Poles	Length (mm)
ASIWJ331-5.0-2P	2	10.5
ASIWJ331-5.0-3P	3	15.5
ASIWJ331-5.0-4P	4	20.5
ASIWJ331-5.0-5P	5	25.5
ASIWJ331-5.0-6P	6	30.5
ASIWJ331-5.0-7P	7	35.5
ASIWJ331-5.0-8P	8	40.5
ASIWJ331-5.0-9P	9	45.5
ASIWJ331-5.0-10P	10	50.5
ASIWJ331-5.0-11P	11	55.5
ASIWJ331-5.0-12P	12	60.5
ASIWJ331-5.0-13P	13	65.5
ASIWJ331-5.0-14P	14	70.5
ASIWJ331-5.0-15P	15	75.5
ASIWJ331-5.0-16P	16	80.5