


Certifications	
	
Material	
Screw	M3 Steel Zinc plated
Wire Guard	Brass, Nickel plated
Pin/plate	Copper Alloy, Tin plated
Housing	PA66 UL94V-0, Green
Electrical	
Standard	UL1059/CSA C22.2 No.158
Rated Voltage	300V
Rated Current	12A
Wire range	24-12AWG
Contact resistance	20mΩ
Insulation resistance	500MΩ/500 Vdc
Withstand Voltage	2000 Vac/1Min
Mechanical	
Temperature range	-30°C~+120°C
Torque	0.5Nm (5Lb-In)
Strip length	7mm
Size	
Pitch	7.62mm
Poles	2P-12P

Item	Positions	Length (mm)
MRT3P7.62-2V01VE	2	13.24
MRT3P7.62-3V01VE	3	20.86
MRT3P7.62-4V01VE	4	28.48
MRT3P7.62-5V01VE	5	36.1
MRT3P7.62-6V01VE	6	43.72
MRT3P7.62-7V01VE	7	51.34
MRT3P7.62-8V01VE	8	58.96
MRT3P7.62-9V01VE	9	66.58
MRT3P7.62-10V01VE	10	74.2
MRT3P7.62-11V01VE	11	81.82
MRT3P7.62-12V01VE	12	89.44