


Certifications	
	
Material	
Pin/Plate	Copper Alloy, Nickel Plated
Spring	Stainless Steel
Housing	PA66 UL94V-0, Green
Electrical	
Standard	UL1059/CSA C22.2 No.158
Rated Voltage	300V
Rated Current	14A
Wire range	24-14AWG
Contact resistance	20mΩ
Insulation resistance	500MΩ/500 Vdc
Withstand Voltage	2000 Vac/1Min
Mechanical	
Temperature range	-30°C~+120°C
Strip length	8mm
Size	
Pitch	5.0/5.08mm
Poles	2P-20P

Item	Positions	Length (mm)
MRT30P5/5.08-2FV	2	20 / 20.32
MRT30P5/5.08-3FV	3	25 / 25.4
MRT30P5/5.08-4FV	4	30 / 30.48
MRT30P5/5.08-5FV	5	35 / 35.56
MRT30P5/5.08-6FV	6	40 / 40.64
MRT30P5/5.08-7FV	7	45 / 45.72
MRT30P5/5.08-8FV	8	50 / 50.8
MRT30P5/5.08-9FV	9	55 / 55.88
MRT30P5/5.08-10FV	10	60 / 60.96
MRT30P5/5.08-11FV	11	65 / 66.04
MRT30P5/5.08-12FV	12	70 / 71.12
MRT30P5/5.08-13FV	13	75 / 76.2
MRT30P5/5.08-14FV	14	80 / 81.28
MRT30P5/5.08-15FV	15	85 / 86.36
MRT30P5/5.08-16FV	16	90 / 91.44
MRT30P5/5.08-17FV	17	95 / 96.52
MRT30P5/5.08-18FV	18	100 / 101.6
MRT30P5/5.08-19FV	19	105 / 106.68
MRT30P5/5.08-20FV	20	110 / 111.76