

- IEC 3 Pole Contactor with 1 NO Auxiliary Contact
- Meets IEC, UL, and CSA standards requirements
- Screw Clamp Terminals for easy wiring
- Other sizes of IEC Contactors available upon request.



Frame Size/Type		CC/CDC65
Number of Poles		3 pole
Coil Voltage	CC65-110	120 Vac
	CC65-230	240 Vac
	CDC65-12	12 Vdc
	CDC65-24	24 Vdc
Rated Operational Voltage Ue		690V
Rated Insulation Voltage Ui		1000V
Rated Frequency		50/60Hz
Rated Impulse Withstand Voltage, Uimp		8kV
Maximum Operating Rate in Operating Cycles per Hour (AC3)		1800 cycles
Durability, Mechanical		12 million operations
Durability, Electrical		2 million operations
Resistive Amperage AC-1, Thermal		100A
Full Load Amperage and Power AC-3, 200/240V		65A
		18.5kW
UL Rating (50/60Hz) Continuous Current		100A
UL Rating (50/60Hz) HP Single Phase 110-120V		5HP
UL Rating (50/60Hz) HP Single Phase 220-240V		15HP
UL Rating (50/60Hz) HP Three Phase 200-208V		25HP
UL Rating (50/60Hz) HP Three Phase 220-240V		30HP
UL Rating (50/60Hz) HP Three Phase 400-480V		50HP
UL Rating (50/60Hz) HP Three Phase 550-600V		60HP
NEMA Size		2
AC Control Weight		0.9kg (31.75oz)
AC Control Size (W/with Aux Contacts x H x D)		55/79 x 106 x 119mm
DC Control Weight		1.2kg (42.33oz)
DC Control Size (W/with Aux Contacts x H x D)		55/79 x 106 x 146.4mm
Screw Clamp Terminals		M6
Wire Range (AWG)		8-3AWG
Wire Type		Stranded/Solid
Torque		35lb-in

