

- IEC 3 Pole Contactor
- Screw Clamp Terminals for easy wiring
- DIN Rail or Panel Mounting
- Other sizes of IEC Contactors available upon request.



Frame Size/Type		CC/CDC40
Number of Poles		3 pole
Coil Voltage	CC40-110	120 Vac
	CC40-230	240 Vac
	CDC40-12	12 Vdc
	CDC40-24	24 Vdc
Rated Operational Voltage Ue		690V
Rated Insulation Voltage Ui		1000V
Rated Frequency		50/60Hz
Rated Impulse Withstand Voltage, Uimp		8kV
Maximum Operating Rate in Operating Cycles per Hour (AC3)		1800 cycles
Durability, Mechanical		12 million operations
Durability, Electrical		2 million operations
Resistive Amperage AC-1, Thermal		60A
Full Load Amperage and Power AC-3, 200/240V		40A
		11kW
UL Rating (50/60Hz) Continuous Current		60A
UL Rating (50/60Hz) HP Single Phase 110-120V		3HP
UL Rating (50/60Hz) HP Single Phase 220-240V		7.5HP
UL Rating (50/60Hz) HP Three Phase 200-208V		15HP
UL Rating (50/60Hz) HP Three Phase 220-240V		15HP
UL Rating (50/60Hz) HP Three Phase 400-480V		30HP
UL Rating (50/60Hz) HP Three Phase 550-600V		30HP
NEMA Size		1
AC Control Weight		0.44kg (15.52oz)
AC Control Size (W/with Aux Contacts x H x D)		45/69 x 83 x 90mm
DC Control Weight		0.6kg (21.16oz)
DC Control Size (W/with Aux Contacts x H x D)		45/69 x 83 x 117.1mm
Screw Clamp Terminals		M5
Wire Range (AWG)		8-6AWG
Wire Type		Stranded/Solid
Torque		35lb-in

