

GFCI Electrical Outlets LTG20 Series 20 A Duplex Receptacle

General Features:

- The unit has individual sets of contacts for GFCI receptacle face and downstream receptacles. No power will be delivered to receptacle face if improperly wired. (Line-load reversed).
- Trip threshold meets UL requirement for tripping time (0.025 seconds).
- Less nuisance tripping due to high frequency noise.
- Provides superior resistance to electrical surges and over-voltages.
- Lockout Action prevents reset if GFCI is damaged or does not respond to a ground fault.
- Status Indicator Lights provide simple, intuitive feedback on power, voltage and protection status as well as end of life.
- Silver alloy contacts.
- Self-test every 120 minutes to ensure continuous safety.
- Impact resistant thermoplastic cover and body.
- One piece T-design trip latch mechanism provides efficient operation.
- TEST and RESET button colors match device face.
- Compatible with all wall boxes and matching wall plates.

Tamper Resistant:

- Complies with NEC® requirement that all 15A and 20A receptacles installed in dwelling units should be tamper resistant
- Receptacles with shutter mechanism blocks access to the contacts unless the plug is fully inserted

Weather Resistant:

- Designed for wet and damp locations, required by NEC® Section 406.8
- Anti-ultraviolet plastics
- Cold impact resistant
- Operating temperature from -30°C to 150°C
- Stainless steel strap and screws

Self Test:

- New Version UL943 Standard now requires newly manufactured GFCI's to be auto-monitoring (self-testing) by conducting an internal test to confirm that protected power is available.
- Provides continuous ground fault protection.
- On initial power up, tests the GFCI within 1 second.
- Self test (auto-monitoring) exceeds the new version UL requirement.
- Testing every two hours updates the protection status.
- Auto adapts and shifts to more frequent testing if potential problem is detected.



Model Number:	Tamper Resistant:	Weather Resistant:
LTG20-W	No	No
LTG20TR-W	Yes	No
LTG20TRWR-W	Yes	Yes
3 and 10 Multi-Packs Now Available Online!		

Specifications:

Voltage:	125V
Current:	20A
Dimensions (H x W x D):	140 x 80 x 50 mm



*Other colors available upon request - Ivory, Almond, Grey and Brown.