

## Snap-In Panel Mount Hydraulic Magnetic Circuit Breaker



DC Medium Delay Trip Curve

Rated Current (Amps)	Part Number
1	NDB3-30Z41-1QHY110L
2	NDB3-30Z42-1QHY110L
3	NDB3-30Z43-1QHY110L
4	NDB3-30Z44-1QHY110L
5	NDB3-30Z45-1QHY110L
6	NDB3-30Z46-1QHY110L
8	NDB3-30Z48-1QHY110L
10	NDB3-30Z410-1QHY110L
12	NDB3-30Z412-1QHY110L
15	NDB3-30Z415-1QHY110L
16	NDB3-30Z416-1QHY110L
20	NDB3-30Z420-1QHY110L
24	NDB3-30Z424-1QHY110L
25	NDB3-30Z425-1QHY110L
30	NDB3-30Z430-1QHY110L

**Features:**

- UL489A Listed
- Easy snap-in mounting
- Medium trip curves
- 1 to 30 amp ratings
- Rocker guard standard
- Black, white or orange rockers
- Easy to read printing
- RoHs compliant

**Provide protection for:**

- Power Supplies
- Office Equipment
- Medical Equipment
- Vending Machines
- Amusement Equipment
- Fitness Equipment
- Telecommunications

**Specifications:**

Number of Poles	1
Rated Voltage	DC 80V
Min. Amp Rating	1A
Max. Amp Rating	30A
Interrupting Capacity	1.0kA
Mechanical Life	10,000 Operations
Operating Temp. Range	-40°C - 85°C
Agency Approvals	UL489A, TUV

