

High Current, DC, Panel & Rack Mount Hydraulic Magnetic Circuit Breakers



Features:

- UL489A Listed
- AC and DC operation
- Screw mounted - M3 x .5mm thread
Screw not Included
- 1 to 100 Amp ratings
- ROHS Compliant
- Easy to read printing

Provide protection for:

- Telecommunications
- Railway locomotive
- Medical Equipment
- UPS Equipment

Rated Current (Amps)	One Pole	Two Pole	Three Pole
1	NDB3100Z41-1LSS1A0L	NDB3100Z41-2LSS1A0L	NDB3100Z41-3LSS1A0L
2	NDB3100Z42-1LSS1A0L	NDB3100Z42-2LSS1A0L	NDB3100Z42-3LSS1A0L
3	NDB3100Z43-1LSS1A0L	NDB3100Z43-2LSS1A0L	NDB3100Z43-3LSS1A0L
4	NDB3100Z44-1LSS1A0L	NDB3100Z44-2LSS1A0L	NDB3100Z44-3LSS1A0L
5	NDB3100Z45-1LSS1A0L	NDB3100Z45-2LSS1A0L	NDB3100Z45-3LSS1A0L
6	NDB3100Z46-1LSS1A0L	NDB3100Z46-2LSS1A0L	NDB3100Z46-3LSS1A0L
8	NDB3100Z48-1LSS1A0L	NDB3100Z48-2LSS1A0L	NDB3100Z48-3LSS1A0L
10	NDB3100Z410-1LSS1A0L	NDB3100Z410-2LSS1A0L	NDB3100Z410-3LSS1A0L
12	NDB3100Z412-1LSS1A0L	NDB3100Z412-2LSS1A0L	NDB3100Z412-3LSS1A0L
15	NDB3100Z415-1LSS1A0L	NDB3100Z415-2LSS1A0L	NDB3100Z415-3LSS1A0L
16	NDB3100Z416-1LSS1A0L	NDB3100Z416-2LSS1A0L	NDB3100Z416-3LSS1A0L
20	NDB3100Z420-1LSS1A0L	NDB3100Z420-2LSS1A0L	NDB3100Z420-3LSS1A0L
24	NDB3100Z424-1LSS1A0L	NDB3100Z424-2LSS1A0L	NDB3100Z424-3LSS1A0L
25	NDB3100Z425-1LSS1A0L	NDB3100Z425-2LSS1A0L	NDB3100Z425-3LSS1A0L
30	NDB3100Z430-1LSS1A0L	NDB3100Z430-2LSS1A0L	NDB3100Z430-3LSS1A0L
35	NDB3100Z435-1LSS1A0L	NDB3100Z435-2LSS1A0L	NDB3100Z435-3LSS1A0L
40	NDB3100Z440-1LSS1A0L	NDB3100Z440-2LSS1A0L	NDB3100Z440-3LSS1A0L
45	NDB3100Z445-1LSS1A0L	NDB3100Z445-2LSS1A0L	NDB3100Z445-3LSS1A0L
50	NDB3100Z450-1LSS1A0L	NDB3100Z450-2LSS1A0L	NDB3100Z450-3LSS1A0L
60	NDB3100Z460-1LSS1A0L	NDB3100Z460-2LSS1A0L	NDB3100Z460-3LSS1A0L
70	NDB3100Z470-1LSS1A0L	NDB3100Z470-2LSS1A0L	NDB3100Z470-3LSS1A0L
80	NDB3100Z480-1LSS1A0L	NDB3100Z480-2LSS1A0L	NDB3100Z480-3LSS1A0L
90	NDB3100Z490-1LSS1A0L	NDB3100Z490-2LSS1A0L	NDB3100Z490-3LSS1A0L
100	NDB3100Z4100-1LSS1A0L	NDB3100Z4100-2LSS1A0L	NDB3100Z4100-3LSS1A0L

Specifications:

Number of Poles	1, 2 & 3
Rated Voltage	1P 250Vac/80Vdc; 2P 125/250Vac/80Vdc; 3P 480Y/277Vac/80Vdc
Min. Amp Rating	1A
Max. Amp Rating	100A
Interrupting Capacity	3kA
Operating Temp. Range	-40°C - 85°C
Agency Approvals	TUV, CE, UL489A, ROHS

