



- 3-phase 400-500 Vac input
- Short circuit, overload, input and output overvoltage protections
- Over temperature protection
- Alarm contact
- High overload capability to ensure the protections selectivity and start-up of heavy loads
- —



NOTE

(1) Standard version (product after September 2019)
 (2) With protective coating that allow installation in environment with extreme conditions (product on demand)
 Please refer to the datasheet for more details



CODE	XCSSL3480W072VAA	XCSSL3480W072VGA
TYPE	CSL3-480W/072V/AA (1)	CSL3-480W/072V/GA (2)
INPUT TECHNICAL DATA		
Input rated voltage	3x 400-500 Vac	3x 400-500 Vac
Input voltage AC	340...550 Vac	340...550 Vac
Input voltage DC	500 - 600 Vdc	500 - 600 Vdc
Frequency	47...63 Hz	47...63 Hz
Current consumption	1.31 A (400 Vac)	1.31 A (400 Vac)
Inrush peak current	22 A	22 A
Power factor	0.76	0.76
Internal protection fuse	—	—
External protection on AC line	MCB: C-4 A / Fuse: T-3.15 A	MCB: C-4 A / Fuse: T-3.15 A
OUTPUT TECHNICAL DATA		
Output rated voltage	72 Vdc ±1%	72 Vdc ±1%
Output adjustable range	60 ... 81 Vdc	60 ... 81 Vdc
Continuous current	6.6 A at 50°C	6.6 A at 50°C
Overload limiting	9 A (max. 12 A constant current)	9 A (max. 12 A constant current)
Short circuit peak current	26A 400 ms On /800 ms Off (HICCUP mode)	26A 400 ms On /800 ms Off (HICCUP mode)
Ripple @ nominal ratings	45 mVpp	45 mVpp
Hold up time	10 ms (400 Vac)	10 ms (400 Vac)
Status indication	LED "DC OK", LED "Stand-by"	LED "DC OK", LED "Stand-by"
Alarm contact	dry contact, max. 1A @ 24 Vdc (Uout >68.4 Vdc)	dry contact, max. 1A @ 24 Vdc (Uout >68.4 Vdc)
Parallel connection	possible	possible
Redundant parallel connection	possible with external ORing diode	possible with external ORing diode
GENERAL TECHNICAL DATA		
Efficiency	91.5% (400 Vac)	91.5% (400 Vac)
Dissipated power	44.6 W (400 Vac)	44.6 W (400 Vac)
Operating temperature range	-20...+70°C (derating -14 W/°C >50°C)	-20...+70°C (derating -14 W/°C >50°C)
Input / output isolation	3 kVac / 60 s (no SELV output)	3 kVac / 60 s (no SELV output)
Input / ground isolation	1.5 kVac / 60 s	1.5 kVac / 60 s
Output / ground isolation	0.5 kVac / 60 s	0.5 kVac / 60 s
Standard / approvals	EN 60950-1	EN 60950-1
EMC Standards	EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4	EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4
Overvoltage category / Pollution degree	II / 2	II / 2
Protection degree	IP 20	IP 20
Connection terminal IN/OUT	4 mm ² / 4 mm ²	4 mm ² / 4 mm ²
Housing material	aluminium	aluminium
Dimension	80x170x127 mm	80x170x127 mm
Approximate weight	1.5 kg	1.5 kg
Mounting information	vertical on a rail, 20 mm from adjacent components	vertical on a rail, 20 mm from adjacent components
APPROVALS		
ACCESSORIES		
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB


- 3-phase 400-500 Vac input
- Short circuit, overload, input and output overvoltage protections
- Over temperature protection
- Alarm contact
- High overload capability to ensure the protections selectivity and start-up of heavy loads
- —



NOTE

(3) With communication port that allow the connection to the net through the external interface XCCI001MB (product on demand)

Please refer to the datasheet for more details



CODE	XCSSL3480W072VAB
TYPE	CSL3-480W/072V/AB (3)
INPUT TECHNICAL DATA	
Input rated voltage	3x 400-500 Vac
Input voltage AC	340...550 Vac
Input voltage DC	500 - 600 Vdc
Frequency	47...63 Hz
Current consumption	1.31 A (400 Vac)
Inrush peak current	22 A
Power factor	0.76
Internal protection fuse	—
External protection on AC line	MCB: C-4 A / Fuse: T-3.15 A
OUTPUT TECHNICAL DATA	
Output rated voltage	72 Vdc ±1%
Output adjustable range	60 ... 81 Vdc
Continuous current	6.6 A at 50°C
Overload limiting	9 A (max. 12 A constant current)
Short circuit peak current	26A 400 ms On /800 ms Off (HICCUP mode)
Ripple @ nominal ratings	45 mVpp
Hold up time	10 ms (400 Vac)
Status indication	LED "DC OK", LED "Stand-by"
Alarm contact	dry contact, max. 1A @ 24 Vdc (Uout >68.4 Vdc)
Parallel connection	possible
Redundant parallel connection	possible with external ORing diode
GENERAL TECHNICAL DATA	
Efficiency	91.5% (400 Vac)
Dissipated power	44.6 W (400 Vac)
Operating temperature range	-20...+70°C (derating -14 W/°C >50°C)
Input / output isolation	3 kVac / 60 s (no SELV output)
Input / ground isolation	1.5 kVac / 60 s
Output / ground isolation	0.5 kVac / 60 s
Standard / approvals	EN 60950-1
EMC Standards	EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4
Overvoltage category / Pollution degree	II / 2
Protection degree	IP 20
Connection terminal IN/OUT	4 mm ² / 4 mm ²
Housing material	aluminium
Dimension	80x170x127 mm
Approximate weight	1.5 kg
Mounting information	vertical on a rail, 20 mm from adjacent components
ACCESSORIES	
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB