



Certifications	
Material	
Screw	M4.0 Steel Zinc Plated
Wire Cage	Copper Alloy, Nickel Plated
Pin/plate	Copper Alloy, Tin Plated
Housing	PA 66 UL94V-0, Green
Electrical	
Standard	UL1059/CSA C22.2 No.158
Rated Voltage	600V
Rated Current	60A
Wire Range	20-6AWG
Contact Resistance	20mΩ
Insulation Resistance	500MΩ/500 Vdc
Withstand Voltage	2000 Vac/1Min
Mechanical	
Temperature Range	-40°C~+130°C
Torque	1.2Nm (10.6Lb-In)
Strip Length	10mm
Size	
Pitch	12.7mm
Poles	1P-16P

Item	Positions	Length
PWT1-P12.7-1	1	12.7
PWT1-P12.7-2	2	25.4
PWT1-P12.7-3	3	38.1
PWT1-P12.7-4	4	50.8
PWT1-P12.7-5	5	63.5
PWT1-P12.7-6	6	76.2
PWT1-P12.7-7	7	88.9
PWT1-P12.7-8	8	101.6
PWT1-P12.7-9	9	114.3
PWT1-P12.7-10	10	127
PWT1-P12.7-11	11	139.7
PWT1-P12.7-12	12	152.4
PWT1-P12.7-13	13	165.1
PWT1-P12.7-14	14	177.8
PWT1-P12.7-15	15	190.5
PWT1-P12.7-16	16	203.2