


## 2-Level DIN Rail Mounted Terminal Block, Screw Clamp

### With electronic components

with UL94V-0 polyamide insulating body

- for overlapped circuits
- possibility to perform cross-connections on both lower and upper levels (DAS.4/A and DAS. 4/B; other versions only on lower level)
- available in grey RAL 7042 and beige RAL 1001 colours



DAS.4/C terminal block

The /GR tag indicates the grey colour version.

<b>grey version</b>	
<b>beige version</b>	
<b>(Ex) version</b>	
<b>TECHNICAL CHARACTERISTICS</b>	
function / type	2-level component-holder
rated cross-section (mm <sup>2</sup> )	4
connecting capacity	
flexible (mm <sup>2</sup> )	0,2 ÷ 6
rigid (mm <sup>2</sup> )	0,2 ÷ 6
max. flexible with ferrule (mm <sup>2</sup> )-ferrule type	4 - WP40/16
rated voltage / rated current / gauge conf. to IEC 60947-7-1	630 V (*) / - / A4
rated voltage / rated current / AWG / tightening torque value UL	-
(Ex e) rated voltage (V)	-
rated impulse withstand voltage / pollution degree	8 KV / 3
insulation stripping length (mm)	9
tightening torque value (test / max) (Nm)	0,5 / 1,2
height / width / thickness (mm)	62 / 64 / 6
height / width / thickness (mm)	70 / 64 / 6
height / width / thickness (mm)	66 / 64 / 6

**DAS.4/.../GR**  
Cat. No. **DS...GR**


**DAS.4/...**  
Cat. No. **DS...**

### APPROVALS


Approval referring to DAS.4 standard version

<b>ACCESSORIES</b>	
End sections	grey beige blue
Permanent cross connection (pre-assembled)	
Switchable cross connection	
Multiple common bar	250 mm
Shunting screw and sleeve	
Coloured partition	red, green, white
Cross connection barrier	red
Test plug socket	
Test plug	
Modular test plug	
End section for modular test plug	
Numbering strip	
Warning plate	on adjacent terminal blocks
Cover for cross-connection	red, blue o white
Marking tag	printed or blank
End bracket	
Mounting rail according to IEC 60715 Std.	


Type	Cat. No.
<b>DAS/PT/GR</b>	DS101GR
<b>DAS/PT</b>	DS101
-	-
<b>PM/41/2</b> poles	PM412
<b>PM/51/3</b> poles	PM513
<b>PM/51/5</b> poles	PM515
<b>PM/51/10</b> poles	PM510
<b>POS/43</b>	POS43
<b>PMP/58</b>	PMP58
<b>CPM/01</b>	CPM01
<b>DFU/7</b>	DU07..
-	-
<b>PSD/A</b>	PD001
<b>SDD/1</b>	DD001
-	-
-	-
-	-
<b>PRP/5</b>	PRP05
<b>CNU/8/61</b>	NU0861
<b>BTU</b> for PR/DIN and PR/3	BT005
<b>BT/DIN/PO</b> for PR/DIN only	BT001
<b>BT/3-BTO</b> for PR/3 only	BT003-BT007
<b>PR/DIN/AC</b> of steel	PRO01
<b>PR/DIN/AS</b> same with slots	PRO04
<b>PR/DIN/AL</b> of aluminium	PRO02
<b>PR/3/AC</b> for PR/DIN and PR/3	PRO03
<b>PR/3/AS</b> same with slots	PRO05




Cat. No. DS111GR - DS111




Cat. No. DS112GR - DS112




Cat. No. DS113GR - DS113




Cat. No. DS114GR - DS114




Cat. No. DS115GR - DS115




Cat. No. DS119GR - DS119




Cat. No. DS130GR - DS130



Cat. No. DS120GR - DS120



Cat. No. DS128GR - DS128



Cat. No. DS129GR - DS129

(\*) The voltage and current ratings given for the various versions are based on the various type of components and to their connections.