


GREY VERSION	EFD.2/GR Cat. No. EFD200GR	EFD.2/CI/GR Cat. No. EFD210GR	EFD.2/E/GR Cat. No. EFD220GR
BLUE VERSION	EFD.2/BL Cat. No. EFD200BL	EFD.2/CI/BL Cat. No. EFD210BL	

TECHNICAL CHARACTERISTICS



Function / type		EFD.2/GR	EFD.2/CI/GR	EFD.2/E/GR
Rated cross-section	(mm ²)	2,5	2,5	2,5
Connecting capacity	Flexible (mm ²)	0,2 ÷ 4	0,2 ÷ 4	0,2 ÷ 4
	Rigid (mm ²)	0,2 ÷ 4	0,2 ÷ 4	0,2 ÷ 4
	Max. flexible with ferrule (mm ²)-ferrule type	2,5 - WP25/14	2,5 - WP25/14	2,5 - WP25/14
Electrical characteristics according to European standard IEC EN 60947-7-1	Maximum voltage AC/DC (V)	800	800	800
	Maximum current (with cable from 2,5mm ²) (A)	22	22	22
	Section Caliber	A3	A3	A3
Electrical characteristics according to UL standard	Maximum voltage AC/DC (V)	600	600	600
	Maximum current (with cable from 2,5mm ²) (A)	20	20	20
	Section Min-Max (AWG)	24-12	24-12	24-12
Electrical characteristics according to ATEX directive and IEC Ex standard	Maximum voltage AC/DC (V)	500	500	500
	Maximum current (with cable from 2,5mm ²) (A)	18	18	18
	Use temperatures MIN / MAX (°C)	-40 +110	-40 +110	-40 +110
Rated impulse withstand voltage / pollution degree		8kV / 3	8kV / 3	8kV / 3
Insulation stripping length	(mm)	9	9	9
Width	(mm)	5,2	5,2	5,2
Length	(mm)	71,6	71,6	71,6
Height mounted on TH35 / 7.5	(mm)	53,8	53,8	53,8
Height mounted on TH35 / 15	(mm)	61,3	61,3	61,3
Insulation material temperature index (EN 60216-1)	(°C)	130	130	130
Plastic material		Polyamide UL94 V0	Polyamide UL94 V0	Polyamide UL94 V0

APPROVALS



ACCESSORIES		TYPE	CAT. NO.	TYPE	CAT. NO.	TYPE	CAT. NO.
End section	grey	EFD.2/PT/GR	EFD201GR	EFD.2/PT/GR	EFD201GR	EFD.2/PT/GR	EFD201GR
	blue	EFD.2/PT/BL	EFD201BL	EFD.2/PT/BL	EFD201BL	EFD.2/PT/BL	EFD201BL
	End section thickness (mm)	1,5		1,5		1,5	
"Easy Bridge" (PTC) cross connection	2 poles	EFB.2/2/R	EFB0202R	EFB.2/2/R	EFB0202R	EFB.2/2/R	EFB0202R
	3 poles	EFB.2/3/R	EFB0203R	EFB.2/3/R	EFB0203R	EFB.2/3/R	EFB0203R
	5 poles	EFB.2/5/R	EFB0205R	EFB.2/5/R	EFB0205R	EFB.2/5/R	EFB0205R
	10 poles	EFB.2/10/R	EFB0210R	EFB.2/10/R	EFB0210R	EFB.2/10/R	EFB0210R
	Rated current carrying capacity of jumper	22A		22A		22A	
Rated current carrying capacity of jumper in ATEX applications	18A		18A		18A		
Coloured partition	red	DFE.2P/R	DFE04	DFE.2P/R	DFE04	DFE.2P/R	DFE04
105mm adhesive numbering strip (20 terminal blocks)		TAM10105AW	TAM10105AW	TAM10105AW	TAM10105AW	TAM10105AW	TAM10105AW
Single marking tag		CNU/10/51	NU1051S	CNU/10/51	NU1051S	CNU/10/51	NU1051S
Single marking tag for pitch insert		CNU/10/51	NU1051S	CNU/10/51	NU1051S	CNU/10/51	NU1051S
End bracket	Screw	BT/3	BT003	BT/3	BT003	BT/3	BT003
	Snap-fit	BTO	BT007	BTO	BT007	BTO	BT007