

ASIUK5RETURN

Universal terminal block on one side
UKJ-4C



UL US CE RoHS

Dimensions			
Width/Thickness/Height	(mm)	46.8 / 6.2 / 57.5	
Screw thread	(mm)	M3	
Tightening torque	(Nm)	0.6-0.8	
Stripping length	(mm)	8	
Technical data			
Voltage	(V)	500	
Max. operating current	(A)	41	
Cross section	(mm ²)	4	
Connection capacity			
Solid conductors	(mm ²)	0.2-6	
Stranded conductors	(mm ²)	0.2-4	
Terminal block	Type	Order no.	
	UKJ-4C	011028	
	BU:Blue UKJ-4C (BU)	011121	
Mounting rail			
Can be installed on the rails both 	TH35-7.5	102001	
	TH35-15	102005	
	G32-15	102002	
	G32-18	102003	
End cover			
For electrical isolation in the end of terminal blocks. 	UKJ-4CG	012010	
	BU:Blue UKJ-4CG (BU)	012060	
Separating disk			
For separation of neighboring bridges, can be fitted later, no loss of pitch. 	UKJ-4CGP	012031	
Fixed bridge			
For cross connection in the terminal center.	2-pos.	UFBI 2-6	013072
	3-pos.	UFBI 3-6	013073
Screw heads with insulation collar or without.	4-pos.	UFBI 4-6	013078
	10-pos.	UFBI 10-6	013002
	2-pos.	UFBI 2-6N	013064
	3-pos.	UFBI 3-6N	013065
	4-pos.	UFBI 4-6N	013066
	10-pos.	UFBI 10-6N	013047
 N: With insulation collar			
Insertion bridge			
For the connection points with conductors, makes level bridge possible. 	2-pos.	UEB 2-6	013019
	3-pos.	UEB 3-6	013027
	10-pos.	UEB 10-6	013013
Marker strip			
Horizontally/Vertically Blank 	UZB 6-10(Blank)		014002
Can be printed 1-600, or the technical data according to your requirements.	Horizontally 	UZB 6-10 (Horizontally)	
	Vertically 	UZB 6-10 (Vertically)	
Switching jumper for 2 terminal blocks 			
Warning label 			
Screwdriver 	YB 0.6 x 3.5		304002