

spring clamp terminal block 2 levels interconnected, 1.5 mm<sup>2</sup>, grey



Series	HMD
Code	HD120GR
Type	HMD.1/CI/GR
HS code	85369010
Colour	grey
<b>TECHNICAL FEATURES</b>	
Function/Type	2 levels with internal connection
Rated cross-section	1.5 mm <sup>2</sup>
<b>Connecting capacity</b>	
Flexible wire	0.2-2.5 mm <sup>2</sup>
Rigid wire	0.2-2.5 mm <sup>2</sup>
Wire with ferrule - ferrule type	1.5 mm <sup>2</sup> – WP15/14
<b>Electrical characteristics according to IEC EN standard</b>	
Maximum voltage AC/DC	500 V
Maximum current (rated cross-section)	16 A
Caliber	B2
<b>Electrical characteristics according to UL Standard</b>	
Maximum voltage AC/DC	600 V
Maximum current (rated cross-section)	15 A
Section (min-max)	26-14 (AWG)
<b>Electrical characteristics according to ATEX directive and IEC Ex standard</b>	
Maximum voltage AC/DC	400 V
Maximum current (rated cross-section)	
Operating temperature Min/Max	-40 °C / +80 °C
Rated impulse withstand voltage / pollution degree	4 kV / 3
Insulation stripping length	10 mm
Width (pitch)	4.2 mm
Length	73 mm
Height mounted on TH35-7.5/TH35-15/G32	59 / 67 / – mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
<b>ACCESSORIES</b>	
<b>End section</b>	
Grey	HMD.1/PT/GR (cod. HD201GR)
Blue	HMD.1/PT (Ex)i (cod. HD301)
Thickness	1.5 mm
<b>Cross-connection</b>	
Model A)	PTC/1/... (cod. PTC01...)
Model B)	–
<b>Rated current carrying capacity IEC/ATEX</b>	
Cross-connection identification strip	PTC/SP (cod. PTC0990)
Coloured partition plate	DFU/7/R (cod. DU07R)
Cross-connection barrier	DFM/500 (cod. DF500)
Test plug	–
Modular test plug	SDH/4 (cod. DH004) – SDH/4P (cod. DH04P)
End section for modular test plug	SH4/PT (cod. DH401)
<b>Marking</b>	
Single marking tag	SHZ/1 (cod. SH004)
Single marking tag for pitch insertion	–
<b>End bracket</b>	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
DIN rail according to IEC 60715/TH35	PR/3/..
<b>APPROVALS AND MARKINGS</b>	