



screw terminal block 1 level fuse-holder, 4 mm<sup>2</sup>, grey

<b>Series</b>	DSF
<b>Code</b>	DA200GR
<b>Type</b>	DSF.4/GR
<b>HS code</b>	85369010
<b>Colour</b>	grey
<b>TECHNICAL FEATURES</b>	
<b>Function/Type</b>	2 levels (fuse-holder + feed-through)
<b>Rated cross-section</b>	4 mm <sup>2</sup>
<b>Connecting capacity</b>	
<b>Flexible wire</b>	0.2-6 mm <sup>2</sup>
<b>Rigid wire</b>	0.2-6 mm <sup>2</sup>
<b>Wire with ferrule - ferrule type</b>	4 mm <sup>2</sup> – WP40/16
<b>Electrical characteristics according to IEC EN standard</b>	
<b>Maximum voltage AC/DC</b>	800 V
<b>Maximum current (rated cross-section)</b>	6.3 (10 A con CO/5) / 32 A (1)
<b>Caliber</b>	A4
<b>Electrical characteristics according to UL Standard</b>	
<b>Electrical characteristics according to ATEX directive and IEC Ex standard</b>	
<b>Rated impulse withstand voltage / pollution degree</b>	8 kV / 3
<b>Insulation stripping length</b>	9 mm
<b>Tightening torque value (nom. / max.)</b>	0.5 / 1.2 Nm
<b>Width (pitch)</b>	8 mm
<b>Length</b>	79.5 mm
<b>Height mounted on TH35-7.5/TH35-15/G32</b>	69 / 77 / – mm
<b>Insulation material temperature index (EN 60216-1)</b>	130 °C
<b>Plastic material</b>	Polyamide UL94V-0
<b>ACCESSORIES</b>	
<b>End section</b>	
<b>Grey</b>	DSF.4/PT/GR (cod. DS401GR)
<b>Blue</b>	–
<b>Beige</b>	DSF.4/PT (cod. DS401)
<b>Thickness</b>	1.5 mm

Cross-connection	
Model A)	-
Model B)	-
Rated current carrying capacity IEC/ATEX	-
Cross-connection identification strip	-
Maximum voltage AC/DC	600 V
Maximum current (rated cross-section)	6.3-20 A
Coloured partition plate	DFU/7/R (cod. DU07R)
Section (min-max)	26-12 (AWG)
Cross-connection barrier	-
Tightening torque value (UL)	4.4 lb.in
Test plug socket	-
Test plug	-
Marking	
Snap-on numbering strip	CNU/8/51 (cod. NU0851S) – CNU/10/61 (cod. NU1061S)
Single marking tag	-
Fuse type	5×20 mm (1)
Conductive element	CO/5 (cod. VL103)
Light alarm circuit (12...48 V)	-
Light alarm circuit (110...230 V)	CIL/115-230 (cod. SF510)
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
IEC 60715/G32	-
<b>APPROVALS AND MARKINGS</b>	