





<b>GREY VERSION</b>	<b>EFT.2/GR</b> Cat. No. EFT200GR	<b>EFT.2/S/GR</b> Cat. No. EFT250GR
<b>BLUE VERSION</b>	<b>EFT.2/BL</b> Cat. No. EFT200BL	

## TECHNICAL CHARACTERISTICS



<b>Function / type</b>			3 levels	3 levels - for sensors
<b>Rated cross-section</b>			2,5	2,5
<b>Connecting capacity</b>	Flexible	[mm²]	0,2 ÷ 4	0,2 ÷ 4
	Rigid	[mm²]	0,2 ÷ 4	0,2 ÷ 4
	Max. flexible with ferrule	[mm²]-ferrule type	2,5 - WP25/14	2,5 - WP25/14
<b>Electrical characteristics according to European standard IEC EN 60947-7</b>	Maximum voltage AC/DC	[V]	800	800
	Maximum current (with cable from 2,5mm²)	[A]	-	-
	Section	Caliber	A3	A3
<b>Electrical characteristics according to UL standard</b>	Maximum voltage AC/DC	[V]	600	600
	Maximum current (with cable from 2,5mm²)	[A]	20	20
	Section Min-Max	[AWG]	24-12	24-12
<b>Electrical characteristics according to ATEX directive and IEC Ex standard</b>	Maximum voltage AC/DC	[V]		
	Maximum current (with cable from 2,5mm²)	[A]	ATEX Pending	ATEX Pending
	Use temperatures MIN / MAX	[°C]		
<b>Rated impulse withstand voltage / pollution degree</b>			8kV / 3	8kV / 3
<b>Insulation stripping length</b>			9	9
<b>Width</b>			5,2	5,2
<b>Length</b>			49,6	76,6
<b>Height mounted on TH35 / 7.5</b>			39,2	39,2
<b>Height mounted on TH35 / 15</b>			46,7	46,7
<b>Insulation material temperature index [EN 60216-1]</b>			130	130
<b>Plastic material</b>			Polyamide UL94 V0	Polyamide UL94 V0

## APPROVALS



<b>ACCESSORIES</b>		<b>TYPE</b>	<b>CAT. NO.</b>	<b>TYPE</b>	<b>CAT. NO.</b>
<b>End section</b>	grey	<b>EFT.2/PT/GR</b>	EFT201GR	<b>EFT.2/S/PT/GR</b>	EFT251GR
	blue	<b>EFT.2/PT/BL</b>	EFT201BL	-	-
	End section thickness	[mm]	<b>1,5</b>	<b>1,5</b>	
<b>"Easy Bridge" (PTC) cross connection</b>	2 poles	<b>EFB.2/2/R</b>	EFB0202R	<b>EFB.2/2/R</b>	EFB0202R
	3 poles	<b>EFB.2/3/R</b>	EFB0203R	<b>EFB.2/3/R</b>	EFB0203R
	5 poles	<b>EFB.2/5/R</b>	EFB0205R	<b>EFB.2/5/R</b>	EFB0205R
	10 poles	<b>EFB.2/10/R</b>	EFB0210R	<b>EFB.2/10/R</b>	EFB0210R
	Rated current carrying capacity of jumper	[A]			
<b>105mm adhesive numbering strip (20 terminal blocks)</b>		<b>TAM10105AW</b>	TAM10105AW	<b>TAM10105AW</b>	TAM10105AW
<b>Single marking tag</b>		<b>CNU/10/51</b>	NU1051S	<b>CNU/10/51</b>	NU1051S
<b>Single marking tag for pitch insert</b>		<b>CNU/10/51</b>	NU1051S	<b>CNU/10/51</b>	NU1051S
<b>End bracket</b>	Screw	<b>BT/3</b>	BT003	<b>BT/3</b>	BT003
	Snap-fit	<b>BTO</b>	BT007	<b>BTO</b>	BT007