








Diode-holders with UL94V-0 polyamide insulating body

- for 1 A diodes (1N4001 ÷ 1N4007 types)
- for 3 A diodes (BY 255 type)
- universal mounting onto both PR/DIN and PR/3 type rails - according to IEC 60715 Std., "G32" and "TH/35" types
- available in grey RAL 7042 and beige RAL 1001 colours


The /GR tag indicates the grey colour version.

grey version	
beige version	
TECHNICAL CHARACTERISTICS	
function / type	
rated cross-section	(mm ²)
connecting capacity	
flexible	(mm ²)
rigid	(mm ²)
max. flexible with ferrule (mm ²)-ferrule type	
rated voltage / rated current / gauge	conf. to IEC 60947-7-1
rated voltage / rated current / AWG / tightening torque value	UL
(Ex e) rated voltage 	(V)
rated impulse withstand voltage / pollution degree	
insulation stripping length	(mm)
tightening torque value (test / max)	(Nm)
height / width / thickness	 TH/35 7,5 mm
height / width / thickness	 TH/35 15 mm
height / width / thickness	 G32
ACCESSORIES	
End sections	grey beige blue
Permanent cross connection	
Switchable cross connection	
Multiple common bar	250 mm
Shunting screw and sleeve	
Coloured partition	red, green, white
Cross connection barrier	red
Test plug socket	
Test plug	
Numbering strip	
Miniature fuse	
Conducting element	
Cartridge / insert with 1A diode	
Cartridge / insert with 3A diode	
Marking tag	printed or blank
End bracket	
Mounting rail	
according to IEC 60715 Std.	



(**) hole suited for the sealing of the lever or for the insertion of a rod, in order to perform simultaneous opening of adjoining levers

(*) value referred to the insulation characteristics of the terminal block

SFR.4/GR	
Cat. No.	SF900GR
SFR.4	
Cat. No.	SF900
function / type	for 1 A or 3 A diodes
rated cross-section	4
connecting capacity	
flexible	0,2 ÷ 6
rigid	0,2 ÷ 6
max. flexible with ferrule (mm ²)-ferrule type	4 - WP40/16
rated voltage / rated current / gauge	800 V (*) / 1 (3) A / A4
rated voltage / rated current / AWG / tightening torque value	-
(Ex e) rated voltage 	6 kV (*) / 3
rated impulse withstand voltage / pollution degree	11
insulation stripping length	0,5 / 1,2
tightening torque value (test / max)	52 / 52 / 8
height / width / thickness	60 / 52 / 8
height / width / thickness	56 / 52 / 8
Type	Cat. No.
SFR/PT/GR	SF701GR
SFR/PT	SF701
SFR/PT (Ex)i	SF801
-	-
-	-
-	-
-	-
-	-
-	-
-	-
-	-
-	-
-	-
SFR/11A (with 1 A diode)	SF992
SFR/13A (with 3 A diode)	SF993
CNU/8/51	NU0851
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BT0 for PR/3 only	BT003-BT007
PR/DIN/AC of steel	PR001
PR/DIN/AS same with slots	PR004
PR/DIN/AL of aluminium	PR002
PR/3/AC for PR/DIN and PR/3	PR003
PR/3/AS same with slots	PR005

The SFR/11A or SFR/3A inserts are supplied as an accessory and are to be mounted in the lever of SFR.4 terminal block, in order to transform it in diode-holder