




GREY VERSION	EFS.2/GR Cat. No. EFS200GR	EFS.4/GR Cat. No. EFS400GR
BLUE VERSION	EFS.2/BL Cat. No. EFS200BL	EFS.4/BL Cat. No. EFS400BL

TECHNICAL CHARACTERISTICS



Function / type		"blade" switchable	"blade" switchable
Rated cross-section	[mm ²]	2,5	4
Connecting capacity	Flexible [mm ²]	0,2 ÷ 4	0,2 ÷ 6
	Rigid [mm ²]	0,2 ÷ 4	0,2 ÷ 6
	Max. flexible with ferrule [mm ²]-ferrule type	2,5 - WP25/14	4 - WP40/16
Electrical characteristics according to European standard IEC EN 60947-7	Maximum voltage AC/DC [V]	630	630
	Maximum current (with cable from 2,5mm ²) [A]	-	-
	Section Caliber	A3	A4
Electrical characteristics according to UL standard	Maximum voltage AC/DC [V]	300	300
	Maximum current (with cable from 2,5mm ²) [A]	12	12
	Section Min-Max [AWG]	24-12	24-12
Rated impulse withstand voltage / pollution degree		8kV / 3	8kV / 3
Insulation stripping length [mm]		9	10
Width [mm]		5,2	6,2
Length [mm]		49,6	55,2
Height mounted on TH35 / 7.5 [mm]		39,2	41,2
Height mounted on TH35 / 15 [mm]		46,7	48,7
Insulation material temperature index (EN 60216-1) [°C]		130	130
Plastic material		Polyamide UL94 V0	Polyamide UL94 V0

APPROVALS



ACCESSORIES		TYPE	CAT. NO.	TYPE	CAT. NO.
End section	grey	EFC.2/PT/GR	EFC201GR	EFC.4/PT/GR	EFC401GR
	blue	EFC.2/PT/BL	EFC201BL	EFC.4/PT/BL	EFC401BL
	End section thickness [mm]	1,5		1,5	
"Easy Bridge" (PTC) cross connection	2 poles	EFB.2/2/R	EFB0202R	EFB.4/2/R	EFB0402R
	3 poles	EFB.2/3/R	EFB0203R	EFB.4/3/R	EFB0403R
	5 poles	EFB.2/5/R	EFB0205R	EFB.4/5/R	EFB0405R
	10 poles	EFB.2/10/R	EFB0210R	EFB.4/10/R	EFB0410R
	Rated current carrying capacity of jumper [A]				
Coloured partition	red	DFE.1+1/R	DFE01	DFE.1+1/R	DFE01
105mm adhesive numbering strip (16 terminal blocks)		TAM10105AW	TAM10105AW	TAM10105AW	TAM10105AW
Single marking tag		CNU/10/51	NU1051S	CNU/10/51	NU1051S
Single marking tag for pitch insert		CNU/10/51	NU1051S	CNU/10/61	NU1061S
End bracket	Screw	BT/3	BT003	BT/3	BT003
	Snap-fit	BTO	BT007	BTO	BT007