

With special connections

- with flat push-on tab connections
- universal mounting for both PR/DIN and PR/3 rails which meet IEC 60715 norms, "G32" and TH/35 types
- available in beige
- maximum operating temperature 100°C



6.3 x 0.8 mm flat push-on tab connections compliant with the IEC 60760 Standard



6.3 x 0.8 mm flat push-on tab connections compliant with the IEC 60760 Standard



with 1.6 x 0.8 mm lug for wrapped wire connections

AFO.2/2+2/TPM Code AF420 with 2.4 x 0.8 mm lug for connections to clamp or to twisted wire


beige version

TECHNICAL CHARACTERISTICS

function/type	
rated cross-section	(mm²)
connecting capacity	
flexible	(mm²)
rigid	(mm²)
rated voltage / rated current / gauge	conf. to IEC 60947-7-1
rated voltage / rated current / AWG / tightening torque value	UL
(Ex e) rated voltage	(V)
rated impulse withstand voltage / pollution degree	
insulation stripping length	(mm)
tightening torque value (test / max)	(Nm)
height / width / thickness	TH/35 7.5 mm
height / width / thickness	TH/35 15 mm
height / width / thickness	G32

AFO.2/1+1

Cat. No. **AF500**



feed-through with push-on tab connections - separate levels	2.5
up to 2.5	
400 V / 20 A / -	
300 V / 15 A / -	
4 kV / 3	
49 / 44 / 6.5	
57 / 44 / 6.5	
52 / 44 / 6.5	

AFO.2/2+2

Cat. No. **AF400**



feed-through with push-on tab connections	2.5
up to 2.5	
630 V / 20 A / -	
600 V / 15 A / -	
6 kV / 3	
49 / 44 / 6.5	
57 / 44 / 6.5	
52 / 44 / 6.5	

AFO.2/2+2/TPM

Cat. No. **AF410**



feed-through with push-on tab connections and lug	2.5
up to 2.5	
320 V / 10 A / -	
4 kV / 3	
49 / 59 / 6.5	
57 / 59 / 6.5	
52 / 59 / 6.5	

APPROVALS



ACCESSORIES

End sections	grey beige blue
Permanent cross connection	
Switchable cross connection	
Multiple common bar	250 mm
Shunting screw and sleeve	
Coloured partition	red, green, white
Cross connection barrier	red
Test plug socket	
Test plug	
Numbering strip	
Cover for cross-connection	
Warning plate	
Marking tag	printed or blank
End bracket	

Type Cat. No.

AFO/PT	AF201
-	
-	
-	
-	
DFU/1	DU01..
-	
-	
-	
-	
CNU/8/51	NU0851
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BTO for PR/3 only	BT003-BT007

Type Cat. No.

AFO/PT	AF201
-	
-	
-	
-	
DFU/1	DU01..
-	
-	
-	
-	
CNU/8/51	NU0851
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BTO for PR/3 only	BT003-BT007

Type Cat. No.

AFO/PT	AF201
-	
-	
-	
-	
DFU/1	DU01..
-	
-	
-	
-	
CNU/8/51	NU0851
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BTO for PR/3 only	BT003-BT007