



## With special connections

- with flat push-on tab connections
- universal mounting for both PR/DIN and PR/3 rails which meet IEC 60715 norms, "G32" and TH/35 types
- available in beige and grey, where indicated
- maximum operating temperature 100°C



6.3 x 0.8 mm, or 2.8 x 0.8 mm, flat push-on tab connections compliant with the IEC 60760 Standard



### Cross-connection possibility

6.3 x 0.8 mm, or 2.8 x 0.8 mm, flat push-on tab connections, compliant with the IEC 60760 Standard



The /GR tag indicates the grey version.

<b>grey version</b>	
<b>beige version</b>	
<b>(Ex)i version</b>	
<b>TECHNICAL CHARACTERISTICS</b>	
function/type	
rated cross-section (mm <sup>2</sup> )	
connecting capacity	
flexible (mm <sup>2</sup> )	
rigid (mm <sup>2</sup> )	
max. flexible with ferrule (mm <sup>2</sup> ) - ferrule type	
rated voltage / rated current / gauge	conf. to IEC 60947-7-1
rated voltage / rated current / AWG / tightening torque value	UL
(Ex e) rated voltage	(V)
rated impulse withstand voltage / pollution degree	
insulation stripping length (mm)	
tightening torque value (test / max) (Nm)	
height / width / thickness	TH/35 7.5 mm
height / width / thickness	TH/35 15 mm
height / width / thickness	G32

<b>PDF.2/GR</b>	Cat. No. <b>PF100GR</b>
<b>PDF.2</b>	Cat. No. <b>PF100</b>



feed-through for push-on tab connections	2.5
up to 2.5	
630 V / 20 A / -	
600 V / 16 A / 20-10 AWG	
6 KV / 3	
50 / 57 / 6.5	
58 / 57 / 6.5	
54 / 57 / 6.5	

<b>FDP.2/GR</b>	Cat. No. <b>FD100GR</b>
<b>FDP.2</b>	Cat. No. <b>FD100</b>



feed-through for push-on tab connections	2.5
up to 2.5	
800 V / 20 A / -	
600 V / 16 A / 20-10 AWG	
8 KV / 3	
49 / 65.5 / 6.5	
57 / 65.5 / 6.5	
53 / 65.5 / 6.5	

<b>CVF.4/GR</b>	Cat. No. <b>CV100 GR</b>
<b>CVF.4</b>	Cat. No. <b>CV100</b>
<b>CVF.4 (Ex)i</b>	Cat. No. <b>CV200</b>



feed-through 1 screw and 3-push-on connections	4
0.2-6	
0.2-6	
4-WP40/16	
800 V / 20 A / A4	
600 V / 20 A / 20-12 AWG / 4.4 lb.in	
8 KV / 3	
11	
52 / 48.5 / 6	
60 / 48.5 / 6	
56 / 48.5 / 6	

## APPROVALS



## ACCESSORIES

End section	grey beige blue
Permanent cross connection (pre-assembled)	
Switchable cross connection	
Multiple common bar	250 mm
Shunting screw and sleeve	
Coloured partition	red, green, white
Cross connection barrier	red
Test plug socket	
Test plug	
Numbering strip	
Cover for connections	
Warning plate	
Marking tag	numbered or neutral
End bracket	

Type	Cat. No.
<b>PDF/PT/GR</b>	PF101GR
<b>PDF/PT</b>	PF101
-	
-	
-	
<b>DFU/5</b>	DU05..
-	
-	
-	
-	
-	
<b>CNU/8/51</b>	NU0851
<b>BTU</b> for PR/DIN and PR/3	BT005
<b>BT/DIN/PO</b> only for PR/DIN	BT001
<b>BT/3-BTO</b> only for PR/3	BT003-BT007

Type	Cat. No.
<b>FDP/PT/GR</b>	FD101GR
<b>FDP/PT</b>	FD101
<b>PH/2.5-4</b>	PH100
-	
-	
-	
<b>DFU/5</b>	DU05..
-	
-	
<b>SDD/1</b>	DD001
-	
-	
<b>CNU/8/51</b>	NU0851
<b>BTU</b> for PR/DIN and PR/3	BT005
<b>BT/DIN/PO</b> only for PR/DIN	BT001
<b>BT/3-BTO</b> only for PR/3	BT003-BT007

Type	Cat. No.
<b>CVF/PT/GR</b>	CV101GR
<b>CVF/PT</b>	CV101
<b>CVF/PT (Ex)i</b>	CV201
<b>PM/40/2</b> poles	PM402
<b>PM/58/42</b> poles	PM584
-	
<b>PMP/58</b>	PMP58
<b>CPM/12</b>	CPM12
<b>DFU/3</b>	DU03..
-	
<b>PSD/A</b>	PD001
<b>SDD/1</b>	DD001
<b>CNU/8/61</b>	NU0861
-	
<b>CNU/8/51</b>	NU0851
<b>BTU</b> for PR/DIN and PR/3	BT005
<b>BT/DIN/PO</b> only for PR/DIN	BT001
<b>BT/3-BTO</b> only for PR/3	BT003-BT007