

Short circuit plates



SCB/6/P0/2 Cat. No. **SB203** Short circuit plate for two adjacent SCB.6 terminal blocks



Short circuit plate for four adjacent SCB.6



SCB/6/P0/4 Cat. No. SB204



terminal blocks



Short circuit plate for four adjacent HSCB.6 terminal blocks





Short circuit plate for two adjacent HSCB.6 terminal blocks

HSCB/6/P0/2

Cat. No. **HB203**

SCB/4/P0/2 Cat. No. SB303 Short circuit plate for two adjacent SCB.4 terminal blocks



SCB/4/P0/4 Cat. No. SB304 Short circuit plate for four adjacent SCB.4 terminal blocks



SCX/P0/2 Cat. No. **SC103** Short circuit plate for two adjacent SCX.10



SCX/PO/4 Cat. No. SC104 Short circuit plate for four adjacent SCX.10

(*) supplied assembled as in position A. In order to be inserted into the slot of the plate, it must be dismounted as in position B, then reassembled and screwed into the body of the terminal block.



Short circuit screws and sleeves



SCB/6/CPM Sleeve to be used with SCB/6/PO link



Sleeve to be used with HSCB/6/PO link



Cat. No. SB305 Sleeve to be used with SCB/4/PO link



SCX/CPM Cat. No. SC105 Sleeve to be used with SCX/PO link (*)

Internal/external cross-connection devices



Screw and sleeve to perform the internal link between the front and back conducting bodies of FVS.4 terminal block.



Screw and sleeve to perform the internal and external link between the front and back conducting bodies of FVS.4 terminal blocks.



Cat. No. **DS107**

internal cross-connection DAS/VCE

Screw and sleeve to perform the internal link between the front and back conducting bodies of DAS.4 terminal blocks.

Terminal blocks suited for Ø 5 x 20 mm or Ø 6 x 32 mm fuses can be used as simple disconnection blocks by

inserting special conducting elements.



Screw and sleeve to perform the internal link between front and back conducting bodies or to externally link the conducting bodies of adjacent terminal blocks, of DAS.4 terminal blocks.

Cat. No. **DS108**

Conducting elements



CO/5 Cat. No. **VL103** Ø 5 x 20 mm - in brass for terminal block

types: SF0.4 - SFR.4 - SFR.6/M - FLD.10/F5 -HMF.4 - VLM.10



SFC/CO Ø 6,3 x 32 mm - in brass for terminal block types: FPC.10 - SFC.10 - SFR.6 - with the option

of inserting an SDD/2 test plug

Screening lug



CBD/SH For the connection of the cable shielding - to be used on terminal blocks type CBD.2, 4,