


HMM Series

- UL94V-0
- disconnects with lever
- mounting onto PR/3 type rails according to IEC 60715 standard, TH/35 type
- available in the standard version (grey) or in a version appropriate for use with "intrinsically safe" (Ex)i circuits (blue), where indicated
- maximum operating temperature 100°C

The /GR tag indicates the grey version.



grey version	HMM.2/1+2/S/GR Cat. No. HMS20GR	HMM.2/2+2/A/GR Cat. No. HM170GR	HMM.2/2+2/S/GR Cat. No. HMS10GR
TECHNICAL CHARACTERISTICS			
function/type	disconnect, 1 input and 2 outputs	disconnect (open), 2 inputs and 2 outputs	disconnect, 2 inputs and 2 outputs
rated cross-section (mm ²)	2.5	2.5	2.5
connecting capacity			
flexible (mm ²)	0.2-4	0.2-4	0.2-4
rigid (mm ²)	0.2-4	0.2-4	0.2-4
max. flexible with ferrule (mm ²) - ferrule type	2.5-WP25/14	2.5-WP25/14	2.5-WP25/14
rated voltage / rated current / gauge conf. to IEC 60947-7-1	400 V / 16 A / A3	400 V / 16 A / A3	400 V / 16 A / A3
rated voltage / rated current / AWG UL	600 V / 20 A / 24-12 AWG	600 V / 20 A / 24-12 AWG	600 V / 20 A / 24-12 AWG
rated impulse withstand voltage / pollution degree	6 kV / 3	6 kV / 3	6 kV / 3
insulation stripping length (mm)	10	10	10
height / width / thickness	48 / 66 / 5.2	37 / 82 / 5.2	48 / 82 / 5.2
height / width / thickness	56 / 66 / 5.2	45 / 82 / 5.2	56 / 82 / 5.2
height / width / thickness	-	-	-
APPROVALS			
ACCESSORIES	Type Cat. No.	Type Cat. No.	Type Cat. No.
End sections	grey HMT.2/1+2/PT/GR HM511GR beige - blue -	HMT.2/2+2/PT/GR HM521GR - -	HMT.2/2+2/PT/GR HM521GR - -
Permanent cross connection	-	-	-
Rated current carrying capacity of jumper (A)	-	-	-
Multiple common bar 250 mm	-	-	-
Shunting screw and sleeve	-	-	-
Coloured partition red, green, white	DFH/2 DH02..	DFH/3 DH03..	DFH/3 DH03..
Cross connection barrier red	-	-	-
Test plug socket	-	-	-
Test plug	SDD/1 DD001	SDD/1 DD001	SDD/1 DD001
Modular test plug	SDH/5 DH005	SDH/5 DH005	SDH/5 DH005
End section for modular test plug	SH5/PT DH501	SH5/PT DH501	SH5/PT DH501
Numbering strip	CNU/8/51 NU0851	CNU/8/51 NU0851	CNU/8/51 NU0851
Screwdriver for activation of the spring	CCH/2.5-4 CCH02	CCH/2.5-4 CCH02	CCH/2.5-4 CCH02
Warning plate on adjacent terminal blocks	-	-	-
Marking tag printed or blank	CNU/8/51 NU0851	CNU/8/51 NU0851	CNU/8/51 NU0851
End bracket	BTU for PR/DIN and PR/3 BT005 BTO BT007 BT/3 for PR/3 only BT003	BTU for PR/DIN and PR/3 BT005 BTO BT007 BT/3 for PR/3 only BT003	BTU for PR/DIN and PR/3 BT005 BTO BT007 BT/3 for PR/3 only BT003