

- disconnects with lever
- possible to create parallel connections
- "Easy Bridge" system: multi-polar cross connection without the need for additional protections
- available in the colours: grey, beige, or in a version appropriate for use with "intrinsically safe" (Ex)i circuits (blue)
- maximum continual operating temperature 100°C



<b>grey version</b>	
<b>beige version</b>	
<b>(Ex)i version</b>	
<b>TECHNICAL CHARACTERISTICS</b>	
function/type	
rated cross-section	(mm <sup>2</sup> )
connecting capacity	
flexible	(mm <sup>2</sup> )
rigid	(mm <sup>2</sup> )
max. flexible with ferrule (mm <sup>2</sup> ) - ferrule type	
rated voltage / rated current / gauge	conf. to IEC 60947-7-1
rated voltage / rated current / AWG / tightening torque value	UL
(Ex e) rated voltage	(V)
rated impulse withstand voltage / pollution degree	
insulation stripping length	(mm)
tightening torque value (test / max)	(Nm)
height / width / thickness	TH/35 7.5 mm
height / width / thickness	TH/35 15 mm

<b>CBS.2/GR</b>	Cat. No. <b>CBS02GR</b>
<b>CBS.2</b>	Cat. No. <b>CBS02</b>
<b>CBS.2 (Ex)i</b>	Cat. No. <b>CBS02I</b>



disconnect lever	2
0.2 - 4	
0.2 - 4	
2 - WP25/14	
630V / 22A / A3	
600 V / 20 A / 20-12 AWG / 3.5 lb.in.	
-	
6 KV (*) / 3	
9	
0.4 / 0.6	
52 / 57 / 5	
60 / 57 / 5	

<b>CBS.4/GR</b>	Cat. No. <b>CBS04GR</b>
<b>CBS.4</b>	Cat. No. <b>CBS04</b>
<b>CBS.4 (Ex)i</b>	Cat. No. <b>CBS04I</b>



disconnect lever	4
0.2 - 6	
0.2 - 6	
4 - WP40/16	
630V / 24A / A4	
600 V / 24 A / 20-10 AWG / 4.4 lb.in.	
-	
6 KV / 3	
10	
0.5 / 0.8	
52 / 57 / 6	
60 / 57 / 6	

## APPROVALS



ACCESSORIES	
End sections	grey beige blue
"Easy Bridge" (PTC) cross connection (intrinsically IPXXB protected once mounted)	2 poles 3 poles
Available also in coloured version (PTP)	5 poles
Ref. p. 131	10 poles
Coloured partition	red, green, white
Cross connection barrier	red
Marking tag	printed or blank
End bracket	

Type	Cat. No.
<b>CB/PT/GR</b>	CB401GR
<b>CB/PT</b>	CB401
<b>CB/PT (Ex)i</b>	CB402
<b>PTC/2/02</b>	PTC0202
<b>PTC/2/03</b>	PTC0203
<b>PTC/2/05</b>	PTC0205
<b>PTC/2/10</b>	PTC0210
<b>PTC/2/00 (50 poles)</b>	PTC0200
<b>DFU/3</b>	DU03
<b>DFM/800</b>	DF800 - DF 900
<b>DFM/900</b>	DF800 - DF 900
<b>CNU/8/51</b>	NU0851
<b>BTU</b> for PR/DIN and PR/3	BT005
<b>BT/DIN/PO</b> for PR/DIN only	BT001
<b>BT/3-BTO</b> for PR/3 only	BT003-BT007

Type	Cat. No.
<b>CB/PT/GR</b>	CB401GR
<b>CB/PT</b>	CB401
<b>CB/PT (Ex)i</b>	CB402
<b>PTC/4/02</b>	PTC0402
<b>PTC/4/03</b>	PTC0403
<b>PTC/4/05</b>	PTC0405
<b>PTC/4/10</b>	PTC0410
<b>PTC/4/00 (42 poles)</b>	PTC0400
<b>DFU/3</b>	DU03
<b>DFM/800</b>	DF800 - DF 900
<b>DFM/900</b>	DF800 - DF 900
<b>CNU/8/61</b>	NU0861
<b>BTU</b> for PR/DIN and PR/3	BT005
<b>BT/DIN/PO</b> for PR/DIN only	BT001
<b>BT/3-BTO</b> for PR/3 only	BT003-BT007