


GREEN/YELLOW VERSION

EFTE.2

Cat. No. EFTE200

TECHNICAL CHARACTERISTICS



Function / type			3 levels + Ground
Rated cross-section		(mm ²)	2,5
Connecting capacity	Flexible	(mm ²)	0,2 ÷ 4
	Rigid	(mm ²)	0,2 ÷ 4
	Max. flexible with ferrule	(mm ²)-ferrule type	2,5 - WP25/14
Electrical characteristics according to European standard IEC EN 60947-7	Maximum voltage AC/DC	(V)	800
	Maximum current (with cable from 2,5mm ²)	(A)	-
	Section	Caliber	A3
Electrical characteristics according to UL standard	Maximum voltage AC/DC	(V)	600
	Maximum current (with cable from 2,5mm ²)	(A)	20
	Section Min-Max	(AWG)	24-12
Electrical characteristics according to ATEX directive and IEC Ex standard	Maximum voltage AC/DC	(V)	
	Maximum current (with cable from 2,5mm ²)	(A)	ATEX Pending
	Use temperatures MIN / MAX	(°C)	
Rated impulse withstand voltage / pollution degree			8kV / 3
Insulation stripping length	(mm)	9	
Width	(mm)	5,2	
Length	(mm)	63,1	
Height mounted on TH35 / 7.5	(mm)	39,2	
Height mounted on TH35 / 15	(mm)	46,7	
Insulation material temperature index (EN 60216-1)	(°C)	130	
Plastic material	Polyamide UL94 V0		

APPROVALS



ACCESSORIES		TYPE	CAT. NO.
End section	grey	EFT.2/PT/GR	EFT201GR
	blue	-	-
	End section thickness (mm)	1,5	
"Easy Bridge" (PTC) cross connection	2 poles	EFB.2/2/R	EFB0202R
	3 poles	EFB.2/3/R	EFB0203R
	5 poles	EFB.2/5/R	EFB0205R
	10 poles	EFB.2/10/R	EFB0210R
	Rated current carrying capacity of jumper (A)		
105mm adhesive numbering strip (20 terminal blocks)		TAM10105AW	TAM10105AW
Single marking tag		CNU/10/51	NU1051S
Single marking tag for pitch insert		CNU/10/51	NU1051S
End bracket	Screw	BT/3	BT003
	Snap-fit	BTO	BT007