





GREY VERSION	EFT.2/GR Cat. No. EFT200GR	EFT.2/S/GR Cat. No. EFT250GR
BLUE VERSION	EFT.2/BL Cat. No. EFT200BL	

TECHNICAL CHARACTERISTICS



Function / type			3 levels	3 levels - for sensors
Rated cross-section			2,5	2,5
Connecting capacity	Flexible	[mm²]	0,2 ÷ 4	0,2 ÷ 4
	Rigid	[mm²]	0,2 ÷ 4	0,2 ÷ 4
	Max. flexible with ferrule	[mm²]-ferrule type	2,5 - WP25/14	2,5 - WP25/14
Electrical characteristics according to European standard IEC EN 60947-7	Maximum voltage AC/DC	[V]	800	800
	Maximum current (with cable from 2,5mm²)	[A]	-	-
	Section	Caliber	A3	A3
Electrical characteristics according to UL standard	Maximum voltage AC/DC	[V]	600	600
	Maximum current (with cable from 2,5mm²)	[A]	20	20
	Section Min-Max	[AWG]	24-12	24-12
Electrical characteristics according to ATEX directive and IEC Ex standard	Maximum voltage AC/DC	[V]		
	Maximum current (with cable from 2,5mm²)	[A]	ATEX Pending	ATEX Pending
	Use temperatures MIN / MAX	[°C]		
Rated impulse withstand voltage / pollution degree			8kV / 3	8kV / 3
Insulation stripping length			9	9
Width			5,2	5,2
Length			49,6	76,6
Height mounted on TH35 / 7.5			39,2	39,2
Height mounted on TH35 / 15			46,7	46,7
Insulation material temperature index [EN 60216-1]			130	130
Plastic material			Polyamide UL94 V0	Polyamide UL94 V0

APPROVALS



ACCESSORIES		TYPE	CAT. NO.	TYPE	CAT. NO.
End section	grey	EFT.2/PT/GR	EFT201GR	EFT.2/S/PT/GR	EFT251GR
	blue	EFT.2/PT/BL	EFT201BL	-	-
	End section thickness	[mm]	1,5	1,5	
"Easy Bridge" (PTC) cross connection	2 poles	EFB.2/2/R	EFB0202R	EFB.2/2/R	EFB0202R
	3 poles	EFB.2/3/R	EFB0203R	EFB.2/3/R	EFB0203R
	5 poles	EFB.2/5/R	EFB0205R	EFB.2/5/R	EFB0205R
	10 poles	EFB.2/10/R	EFB0210R	EFB.2/10/R	EFB0210R
	Rated current carrying capacity of jumper	[A]			
105mm adhesive numbering strip (20 terminal blocks)		TAM10105AW	TAM10105AW	TAM10105AW	TAM10105AW
Single marking tag		CNU/10/51	NU1051S	CNU/10/51	NU1051S
Single marking tag for pitch insert		CNU/10/51	NU1051S	CNU/10/51	NU1051S
End bracket	Screw	BT/3	BT003	BT/3	BT003
	Snap-fit	BTO	BT007	BTO	BT007