



UKJ ground terminal blocks meet international IEC 60947-7-2 standards , connection capacity: 0.22-95mm<sup>2</sup> .

**Features:**











- 1.Can be installed on the rails both  and  .
- 2.Colors according to international standards (yellow and green).

**ASIUSLKG1.5N**

Ground terminal block  
**UKJ-1.5JD**



UL us CE ENEC RoHS


Dimensions		
Width/Thickness/Height	(mm)	42.5 / 4.2 / 40.6
Screw thread	(mm)	M2
Tightening torque	(Nm)	0.22-0.25
Stripping length	(mm)	7
Technical data		
Cross section	(mm <sup>2</sup> )	1.5
Connection capacity		
Solid conductors	(mm <sup>2</sup> )	0.14-1.5
Stranded conductors	(mm <sup>2</sup> )	0.14-1.5
Terminal block		
	Type	Order no.
	UKJ-1.5JD	011026
Mounting rail		
Can be installed on the rails both  and 		TH35-7.5
		TH35-15
		G32-15
		G32-18
		102001
		102005
		102002
		102003
Marker strip		
Horizontally/Vertically	Blank 	UZH 4-10 (Blank)
Can be printed 1-600, or the technical data according to your requirements.	Horizontally 	UZH 4-10 (Horizontally)
	Vertically 	UZH 4-10 (Vertically)
Screwdriver		YB 0.4 x 2.5
		304001

**Notes:**

If it is placed next to a feed-through terminal block of the same shape, an end cover must be placed between the two when the voltage is greater than 690V.

## ASIUSLKG5


Ground terminal block  
UKJ-4JD



UL US CE CQC RoHS

## ASIUSLKG6N

Ground terminal block  
UKJ-6JD



UL US CE CQC RoHS

Dimensions					
Width/Thickness/Height	(mm)	42.5 / 6.2 / 46		42.5 / 8.2 / 46	
Screw thread	(mm)	M3		M4	
Tightening torque	(Nm)	0.6-0.8		1.5-1.8	
Stripping length	(mm)	9		10	
Technical data					
Cross section	(mm <sup>2</sup> )	6		10	
Connection capacity					
Solid conductors	(mm <sup>2</sup> )	0.2-6		0.2-10	
Stranded conductors	(mm <sup>2</sup> )	0.2-4		0.2-6	
Terminal block	Type	Order no.	Type	Order no.	
	UKJ-4JD	011008	UKJ-6JD	011009	
Mounting rail	Can be installed on the rails both  and				
	TH35-7.5	102001	TH35-7.5	102001	
	TH35-15	102005	TH35-15	102005	
	G32-15	102002	G32-15	102002	
	G32-18	102003	G32-18	102003	
Marker strip	Can be printed 1-600, or the technical data according to your requirements.				
Horizontally/Vertically	Blank	UZB 6-10 (Blank)	014002	UZB 8-10 (Blank)	014003
	Horizontally	UZB 6-10 (Horizontally)	014007	UZB 8-10 (Horizontally)	014009
	Vertically	UZB 6-10 (Vertically)	014008	UZB 8-10 (Vertically)	014010
Screwdriver		YB 0.6×3.5	304002	YB 1.0×4.0	

## ASIUSLKG2.5

Ground terminal block  
UKJ-2.5XJD



UL US CE RoHS

## ASIUSLKG2.5N

Ground terminal block  
UKJ-2.5JD



UL US CE RoHS


Dimensions					
Width/Thickness/Height	(mm)	42.5 / 6.2 / 40.6		42.5 / 5.2 / 46	
Screw thread	(mm)	M3		M3	
Tightening torque	(Nm)	0.6-0.8		0.6-0.8	
Stripping length	(mm)	7		8	
Technical data					
Cross section	(mm <sup>2</sup> )	4		4	
Connection capacity					
Solid conductors	(mm <sup>2</sup> )	0.2-4		0.2-4	
Stranded conductors	(mm <sup>2</sup> )	0.2-2.5		0.2-2.5	
Terminal block	Type	Order no.	Type	Order no.	
	UKJ-2.5XJD	011038	UKJ-2.5JD	011007	
Mounting rail					
Can be installed on the rails both					
	TH35-7.5	102001	TH35-7.5	102001	
	TH35-15	102005	TH35-15	102005	
	G32-15	102002	G32-15	102002	
	G32-18	102003	G32-18	102003	
Marker strip					
Horizontally/Vertically	Blank	UZB 6-10 (Blank)	014002	UZB 5-10 (Blank)	014001
Can be printed 1-600, or the technical data according to your requirements.	Horizontally	UZB 6-10 (Horizontally)	014007	UZB 5-10 (Horizontally)	014005
	Vertically	UZB 6-10 (Vertically)	014008	UZB 5-10 (Vertically)	014006
Screwdriver		YB 0.6×3.5	304002	YB 0.6×3.5	304002

### Notes:

If it is placed next to a feed-through terminal block of the same shape, an end cover must be placed between the two when the voltage is greater than 690V.

### ASIUK3TWINPE


Ground terminal block with 3 connections  
UKJ-2.5/1 × 2JD



UL US CE CCC RoHS

### ASIUK5TWINPE


Ground terminal block with 3 connections  
UKJ-4/1 × 2JD



CE CCC RoHS

### ASIUDK4PE

Ground terminal block with 4 connections  
UKJ-4/2 × 2JD




UL US CE CCC RoHS

Dimensions							
Width/Thickness/Height	(mm)	50.5 / 5.2 / 47		50.5 / 6.2 / 47		63.6 / 6.2 / 47	
Screw thread	(mm)	M3		M3		M3	
Tightening torque	(Nm)	0.6-0.8		0.6-0.8		0.6-0.8	
Stripping length	(mm)	8		8		8	
Technical data							
Cross section	(mm <sup>2</sup> )	2.5		4		4	
Connection capacity							
Solid conductors	(mm <sup>2</sup> )	0.2-2.5		0.2-4		0.2-6	
Stranded conductors	(mm <sup>2</sup> )	0.2-2.5		0.2-4		0.2-4	
Terminal block	Type	Order no.	Type	Order no.	Type	Order no.	
	UKJ-2.5/1 × 2JD	011041	UKJ-4/1 × 2JD	011042	UKJ-4/2 × 2JD	011033	
Mounting rail							
Can be installed on the rails both and	TH35-7.5	102001	TH35-7.5	102001	TH35-7.5	102001	
	TH35-15	102005	TH35-15	102005	TH35-15	102005	
	G32-15	102002	G32-15	102002	G32-15	102002	
	G32-18	102003	G32-18	102003	G32-18	102003	
Marker strip							
Horizontally/Vertically	Blank	UZB 5-10(Blank)	014001	UZB 6-10(Blank)	014002	UZB 6-10(Blank)	014002
Can be printed 1-600, or the technical data according to your requirements.	Horizontally	UZB 6-10(Horizontally)	014005	UZB 6-10(Horizontally)	014007	UZB 6-10(Horizontally)	014007
	Vertically	UZB 6-10(Vertically)	014006	UZB 6-10(Vertically)	014008	UZB 6-10(Vertically)	014008
Screwdriver		YB 0.6 × 3.5	304002	YB 0.6 × 3.5	304002	YB 0.6 × 3.5	304002

### ASIUSLKG10N

Ground terminal block  
UKJ-10JD



cULus CE CCC RoHS

### ASIUSLKG16N

Ground terminal block  
UKJ-16JD



cULus CE CCC RoHS

### ASIUSLKG35

Ground terminal block  
UKJ-35JD



CE CCC RoHS


Dimensions							
Width/Thickness/height	(mm)	42.5 / 10.2 / 46		42.5 / 12.5 / 53		50.2 / 15 / 61	
Screw thread	(mm)	M4		M4		M6	
Tightening torque	(Nm)	1.5-1.8		1.5-1.8		3.2-3.7	
Stripping length	(mm)	10		11		15	
Technical data							
Cross section	(mm <sup>2</sup> )	16		25		50	
Connection capacity							
Solid conductors	(mm <sup>2</sup> )	0.5-16		2.5-25		0.75-50	
Stranded conductors	(mm <sup>2</sup> )	0.5-10		4-16		0.75-35	
Terminal block	Type	Order no.	Type	Order no.	Type	Order no.	
	UKJ-10JD	011010	UKJ-16JD	011011	UKJ-35JD	011012	
Mounting rail							
Can be installed on the rails both and		TH35-7.5	102001	TH35-7.5	102001	TH35-7.5	102001
		TH35-15	102005	TH35-15	102005	TH35-15	102005
		G32-15	102002	G32-15	102002	G32-15	102002
		G32-18	102003	G32-18	102003	G32-18	102003
Marker strip							
Horizontally/Vertically	Blank	UZB 10-10(Blank)	014004	UZB 10-10(Blank)	014004	UZB 10-10(Blank)	014004
Can be printed 1-600, or the technical data according to your requirements.	Horizontally	UZB 10-10(Horizontally)	014011	UZB 10-10(Horizontally)	014011	UZB 10-10(Horizontally)	014011
	Vertically	UZB 10-10(Vertically)	014012	UZB 10-10(Vertically)	014012	UZB 10-10(Vertically)	014012
Screwdriver		YB 1.0x4.0		YB 1.0x4.0		YB 1.0x6.5	

**Notes:**

If it is placed next to a feed-through terminal block of the same shape, an end cover must be placed between the two when the voltage is greater than 690V.

## ASIMT1.5PE

Miniature ground terminal block  
UKJ-1.5MTJD



CE RoHS

## ASIMT1.5TWINPE


Miniature ground terminal block  
with 3 connections  
UKJ-1.5MT/1×2JD



CE RoHS

## ASIMT1.5QUATTROPE

Miniature ground terminal block  
with 4 connections  
UKJ-1.5MT/2×2JD



CE RoHS

Dimensions		CE RoHS		CE RoHS		CE RoHS	
Width/Thickness/Height	(mm)	22.2 / 4.2 / 22.5		28 / 4.2 / 29.5		33.5 / 4.2 / 29.5	
Screw thread	(mm)	M2		M2		M2	
Tightening torque	(Nm)	0.22-0.25		0.22-0.25		0.22-0.25	
Stripping length	(mm)	6		6		6	
Technical data		CE RoHS		CE RoHS		CE RoHS	
Cross section	(mm <sup>2</sup> )	1.5		1.5		1.5	
Connection capacity		CE RoHS		CE RoHS		CE RoHS	
Solid conductors	(mm <sup>2</sup> )	0.14-1.5		0.14-1.5		0.14-1.5	
Stranded conductors	(mm <sup>2</sup> )	0.14-1.5		0.14-1.5		0.14-1.5	
Terminal block	Type	Order no.	Type	Order no.	Type	Order no.	
	UKJ-1.5MTJD	011047	UKJ-1.5MT/1×2JD	011048	UKJ-1.5MT/2×2JD	011049	
Mounting rail	TH15-5.5		TH15-5.5		TH15-5.5		
Can be installed on the rails.	102004		102004		102004		
Marker strip	UZBM 4-10(Blank)		UZBM 4-10(Blank)		UZBM 4-10(Blank)		
Horizontally/Vertically	Blank	014016	UZBM 4-10(Blank)	014016	UZBM 4-10(Blank)	014016	
Can be printed 1-600, or the technical data according to your requirements.	Horizontally	UZBM 4-10(Horizontally)	UZBM 4-10(Horizontally)	UZBM 4-10(Horizontally)	UZBM 4-10(Horizontally)	UZBM 4-10(Horizontally)	
	Vertically	UZBM 4-10 (Vertically)	UZBM 4-10 (Vertically)	UZBM 4-10 (Vertically)	UZBM 4-10 (Vertically)	UZBM 4-10 (Vertically)	
Screwdriver	YB 0.4×2.5	304001	YB 0.4×2.5	304001	YB 0.4×2.5	304001	

## ASIMBK5EZPE


Miniature ground terminal block  
**UKJ-4MJD**



CE RoHS

## ASIMSLKG6

Miniature ground terminal block  
**UKJ-6MJD**



CE RoHS

Dimensions					
Width/Thickness/Height	(mm)	28.5 / 6.2 / 30.4		39 / 8.2 / 34.4	
Screw thread	(mm)	M3		M4	
Tightening torque	(Nm)	0.6-0.8		1.5-1.8	
Stripping length	(mm)	8		10	
Technical data					
Cross section	(mm <sup>2</sup> )	6		10	
Connection capacity					
Solid conductors	(mm <sup>2</sup> )	0.2-6		0.5-10	
Stranded conductors	(mm <sup>2</sup> )	0.2-4		0.5-6	
Terminal block		Type	Order no.	Type	Order no.
		UKJ-4MJD	011054	UKJ-6MJD	011055
Mounting rail					
Can be installed on the rails.					
		TH15-5.5	102004	TH15-5.5	102004
Marker strip					
Horizontally/Vertically					
Blank		UZB 6-10(Blank)		014002	
UZB 8-10(Blank)				014003	
Can be printed 1-600, or the technical data according to your requirements.		Horizontally		UZB 6-10(Horizontally)	
		1 2 3 4 5 6 7		014007	
		Vertically		UZB 6-10 (Vertically)	
		1 2 3 4 5 6 7		014008	
Screwdriver		YB 0.6×3.5		304002	
				YB 1.0×4.0	