

## Ring Lug Terminal Block ASIST10


## Ring Lug Terminal Block Conectores para Terminal Ojal

The ASIST series of DIN rail mounted terminal blocks is a complete family of modular terminal blocks ranging in size from 1.5mm to 25mm for feed-through wiring. Also included are double level blocks to save space in the panel, multiple connection blocks to reduce wire and terminal block jumpers, fuse blocks and a sliding link block for control transformer and other electrical circuits. The ASIST series is ideal for industries such as electric utilities, switchgear and electrical panel manufacturers and others that require a ring tongue terminal on the wire to insure a secure connection.

The ASIST series of ring lug terminal blocks has more features than competing terminal blocks and are made of higher quality materials, such as UL94V0 polyamide housings. Features include:


- Housing material rated at UL94V0.
- Screw accepts both slotted and Phillips head screwdriver.
- Screw is nickel plated to insure better corrosion protection.
- Flat and locking washers are standard and provide better contact to terminal and locks terminal in place.
- Terminal blocks accept a jumper internally for connecting adjacent terminal blocks.
- Current carrying bar is over 75% bigger than the competition to insure maximum current handling capability.
- Large marking strips provide easy labeling and they snap onto the blocks in strips of 10 to save time.
- Double level and multiple connection blocks are available.
- Fuse blocks are available.
- Sliding link disconnect blocks are available.

Specifications				
c <b>SN</b> us				
Screw Size / Rosca				
Tlghtening Torque / Par de apriete				
Ordering Information				
Terminal block, standard	Beige/Bege			
Accessories / Accesorios				
End Cover / Tapa	Beige/Bege			
Circuit bridges, pre-assembled internal bridge Puentes conectores 2 position 3 position 10 position				
External Bridges / Puentes Externos	2 position 3 position			
Marker System, strip of 10 blank markers				



12-10 AWG

Yello



Terminal width .63" (15.5mm) Terminal espresor

	ASIST10		
	Wire RANGE Sección Transversal	CURRENT (A) Corriente	Voltage (V) Tensión
	20 - 6 AWG	65	600
		M6	
	28.5-32.5 Lb In.		
		CATALOG NO.	Pcs/Pkg
		ASI271008	50
		CATALOG NO.	Pcs/Pkg
		ASI272003	25
		ASI273010 ASI273011 ASI273012	25 25 10
		ASI274010 ASI274011	25 25
5 7 D I~		ASI274011 ASI274012	25
		ASIUD1B	25
		ASIUKJBJ	10
er er		PR005 PR005-1M	1 1
		ASI305001	1
C V		RV1.25-6 RV2-6 RV3.5-6 RV5.5-6	100 100 100 100
( V		SVL1.25-6 SVL2-6 SV3.5-6 SV5.5-6	100 100 100 100
_			

## www.SourceASI.com