



P	L (mm)	X
5	(5 x p)+1,2	3,1

Certifications	
Material	
Pin/Plate	Brass, Tin plated
Housing	PA68 UL94V-0, Green
Electrical	
Standard	UL1059/CSA C22.2 No.158
Rated Voltage	300V
Rated Current	16A
Wire range	-
Contact resistance	20mΩ
Insulation resistance	500MΩ/500 Vdc
Withstand Voltage	2000 Vac/1Min
Mechanical	
Temperature range	-30°C~+105°C
Torque	-
Strip length	-
Size	
Pitch	5.0/5.08
Poles	2P-24P Additional sizes available on request

Item	Positions	Length (mm) 5.0/5.08
CPM5.0/5.08-2VE	2	11.2 / 11.36
CPM5.0/5.08-3VE	3	16.2 / 16.44
CPM5.0/5.08-4VE	4	21.2 / 21.52
CPM5.0/5.08-5VE	5	26.2 / 26.6
CPM5.0/5.08-6VE	6	31.2 / 31.68
CPM5.0/5.08-7VE	7	36.2 / 36.76
CPM5.0/5.08-8VE	8	41.2 / 41.84
CPM5.0/5.08-9VE	9	46.2 / 46.92
CPM5.0/5.08-10VE	10	51.2 / 52
CPM5.0/5.08-11VE	11	56.2 / 57.08
CPM5.0/5.08-12VE	12	61.2 / 62.16
CPM5.0/5.08-13VE	13	66.2 / 67.24
CPM5.0/5.08-14VE	14	71.2 / 72.32
CPM5.0/5.08-15VE	15	76.2 / 77.4
CPM5.0/5.08-16VE	16	81.2 / 82.48
CPM5.0/5.08-17VE	17	86.2 / 87.56
CPM5.0/5.08-18VE	18	91.2 / 92.64
CPM5.0/5.08-19VE	19	96.2 / 97.72
CPM5.0/5.08-20VE	20	101.2 / 102.8
CPM5.0/5.08-21VE	21	106.2 / 107.88
CPM5.0/5.08-22VE	22	111.2 / 112.96
CPM5.0/5.08-23VE	23	116.2 / 118.04
CPM5.0/5.08-24VE	24	121.2 / 123.12