



Certification	
Material	
Pin/Plate	Copper Alloy, Tin Plated
Housing	PA66, UL 94V-0, Green
Electrical	
Standard	UL 1059/CSA C22.2 No. 158
Rated Voltage	300 V
Rated Current	8 A
Contact Resistance	20mΩ
Insulation Resistance	500MΩ/500 Vdc
Withstand Voltage	2000 Vac/1 Min
Mechanical	
Temperature Range	-40°C...+105°C
Size	
Pitch	3.5 mm (.138")
Poles	2P-16P. Additional sizes available on request.

Item	No. of Poles	Length (mm)
ASIWJ15EDGVH-3.5-2P	2	8.2
ASIWJ15EDGVH-3.5-3P	3	11.7
ASIWJ15EDGVH-3.5-4P	4	15.2
ASIWJ15EDGVH-3.5-5P	5	18.7
ASIWJ15EDGVH-3.5-6P	6	22.2
ASIWJ15EDGVH-3.5-7P	7	25.7
ASIWJ15EDGVH-3.5-8P	8	29.2
ASIWJ15EDGVH-3.5-9P	9	32.7
ASIWJ15EDGVH-3.5-10P	10	36.2
ASIWJ15EDGVH-3.5-11P	11	39.7
ASIWJ15EDGVH-3.5-12P	12	43.2
ASIWJ15EDGVH-3.5-13P	13	46.7
ASIWJ15EDGVH-3.5-14P	14	50.2
ASIWJ15EDGVH-3.5-15P	15	53.7
ASIWJ15EDGVH-3.5-16P	16	57.2