



Certifications	
	
Material	
Screw	M2.5 Steel Zinc plated
Wire Guard	Stainless Steel
Pin/plate	Copper Alloy, Tin plated
Housing	PA66 UL94V-0, Green
Electrical	
Standard	UL1059/CSA C22.2 No.158
Rated Voltage	300V
Rated Current	8A
Wire range	26-14AWG
Contact resistance	20mΩ
Insulation resistance	500MΩ/500 Vdc
Withstand Voltage	2000 Vac/1Min
Mechanical	
Temperature range	-40°C~+105°C
Torque	0.25Nm (2.2Lb-in)
Strip length	6-7mm (0.24-0.28")
Size	
Pitch [ mm ]	5mm(.197")
Poles	2P-20P. Additional sizes available on request

Item	Positions	Length (mm)
ASIWJ126-5.0-2P	2	10
ASIWJ126-5.0-3P	3	15
ASIWJ126-5.0-4P	4	20
ASIWJ126-5.0-5P	5	25
ASIWJ126-5.0-6P	6	30
ASIWJ126-5.0-7P	7	35
ASIWJ126-5.0-8P	8	40
ASIWJ126-5.0-9P	9	45
ASIWJ126-5.0-10P	10	50
ASIWJ126-5.0-11P	11	55
ASIWJ126-5.0-12P	12	60
ASIWJ126-5.0-13P	13	65
ASIWJ126-5.0-14P	14	70
ASIWJ126-5.0-15P	15	75
ASIWJ126-5.0-16P	16	80
ASIWJ126-5.0-17P	17	85
ASIWJ126-5.0-18P	18	90
ASIWJ126-5.0-19P	19	95
ASIWJ126-5.0-20P	20	100