



Certifications	
	
Material	
Screw	M2.5 Steel Zinc Plate
Wire Cage	Copper Alloy, Nickel Plated
Pin/Plate	Copper Alloy, Tin plated
Housing	PA 66 UL94V-0, Gray
Electrical	
Standard	UL1059/CSA C22.2 No.158
Rated Voltage	300V
Rated Current	18A
Wire Range	30-12AWG
Contact Resistance	20mΩ
Insulation Resistance	500MΩ/500 Vdc
Withstand Voltage	2000 Vac/1Min
Mechanical	
Temperature Range	-30°C~+120°C
Torque	0.5Nm(4.4 lb/in)
Strip Length	7mm
Size	
Pitch	5mm
Poles	2P-24P

Item	Positions	Length (mm)
CBL5-2	2	10
CBL5-3	3	15
CBL5-4	4	20
CBL5-5	5	25
CBL5-6	6	30
CBL5-7	7	35
CBL5-8	8	40
CBL5-9	9	45
CBL5-10	10	50
CBL5-11	11	55
CBL5-12	12	60
CBL5-13	13	65
CBL5-14	14	70
CBL5-15	15	75
CBL5-16	16	80
CBL5-17	17	85
CBL5-18	18	90
CBL5-19	19	95
CBL5-20	20	100
CBL5-21	21	105
CBL5-22	22	110
CBL5-23	23	115
CBL5-24	24	120