


| Certifications  |                             |
|---|-----------------------------|
|  |                             |
| Material  |                             |
| Screw   | M3 Steel Zinc Plate         |
| Wire Cage   | Copper Alloy, Nickel Plated |
| Pin/Plate   | Copper Alloy, Tin plated    |
| Housing   | PA 66 UL94V-0, Green        |
| Electrical  |                             |
| Standard  | UL1059/CSA C22.2 No.158     |
| Rated Voltage   | 300V                        |
| Rated Current   | 14A                         |
| Wire Range  | 30-14AWG                    |
| Contact Resistance  | 20mΩ                        |
| Insulation Resistance   | 500MΩ/500 Vdc               |
| Withstand Voltage   | 2000 Vac/1Min               |
| Mechanical  |                             |
| Temperature Range   | -30°C~+120°C                |
| Torque  | 0.5Nm(4.4 lb/in)            |
| Strip Length  | 6mm                         |
| Size  |                             |
| Pitch   | 5/5.08mm                    |
| Poles   | 2P-3P                       |

| Item          | Positions | Length (mm) |
|---------------|-----------|-------------|
| CII5/5.08-2VE | 2         | 10 / 10.16  |
| CII5/5.08-3VE | 3         | 15 / 15.24  |