



Certifications	
	
Material	
Screw	M3 Steel Zinc Plate
Wire Cage	Copper Alloy, Nickel Plated
Pin/Plate	Copper Alloy, Tin plated
Housing	PA 66 UL94V-0, Green
Electrical	
Standard	UL1059/CSA C22.2 No.158
Rated Voltage	300V
Rated Current	10A
Wire Range	30-16AWG
Contact Resistance	20mΩ
Insulation Resistance	500MΩ/500 Vdc
Withstand Voltage	2000 Vac/1Min
Mechanical	
Temperature Range	-30°C~+120°C
Torque	0.3Nm(2.7 lb/in)
Strip Length	6mm (0.24-0.28")
Size	
Pitch	7/7.62mm
Poles	2P-12P

Item	Positions	Length (mm)
CPA7/7.62-2VE	2	10.5 / 11.43
CPA7/7.62-3VE	3	17.5 / 19.05
CPA7/7.62-4VE	4	24.5 / 26.67
CPA7/7.62-5VE	5	31.5 / 34.29
CPA7/7.62-6VE	6	38.5 / 41.91
CPA7/7.62-7VE	7	45.5 / 49.53
CPA7/7.62-8VE	8	52.5 / 57.15
CPA7/7.62-9VE	9	59.5 / 64.77
CPA7/7.62-10VE	10	66.5 / 72.39
CPA7/7.62-11VE	11	73.5 / 80.01
CPA7/7.62-12VE	12	80.5 / 87.63