



Certification	
Material	
Locking Nut	M2.5, Copper Alloy
Pin	Copper Alloy, Tin Plated
Housing	PA66, UL 94V-0, Green
Electrical	
Standard	UL 1059/CSA C22.2 No. 158
Rated Voltage	300 V
Rated Current	15 A
Contact Resistance	20mΩ
Insulation Resistance	500MΩ/500 Vdc
Withstand Voltage	2000 Vac/1 Min
Mechanical	
Temperature Range	-40°C...+105°C
Size	
Pitch	7.5 mm (.295")
Poles	2P-12P. Additional sizes available on request.

Item	No. of Poles	Length (mm)
ASIWJ2EDGRM-7.5-2P	2	25.5
ASIWJ2EDGRM-7.5-3P	3	33
ASIWJ2EDGRM-7.5-4P	4	40.5
ASIWJ2EDGRM-7.5-5P	5	48
ASIWJ2EDGRM-7.5-6P	6	55.5
ASIWJ2EDGRM-7.5-7P	7	63
ASIWJ2EDGRM-7.5-8P	8	70.5
ASIWJ2EDGRM-7.5-9P	9	78
ASIWJ2EDGRM-7.5-10P	10	85.5
ASIWJ2EDGRM-7.5-11P	11	93
ASIWJ2EDGRM-7.5-12P	12	100.5