


Certifications	
	
Material	
Pin/plate	Copper Alloy, Tin plated
Housing	PA66 UL94V-0, Orange/Gray
Electrical	
Standard	UL1059/CSA C22.2 No.158
Rated Voltage	300V
Rated Current	10A
Wire range	30-16AWG
Contact resistance	20mΩ
Insulation resistance	500MΩ/500 Vdc
Withstand Voltage	2000 Vac/1Min
Mechanical	
Temperature range	-40°C~+110°C
Strip length	7mm (0.28")
Size	
Pitch	7.5mm /7.62mm
Poles	2P-12P. Additional sizes available on request

Item	Positions	Length (mm) 7.5 / 7.62
MRT1P-7.5/7.62-2P	2	14/14.24
MRT1P-7.5/7.62-3P	3	21.5/21.86
MRT1P-7.5/7.62-4P	4	29/29.48
MRT1P-7.5/7.62-5P	5	36.5/37.1
MRT1P-7.5/7.62-6P	6	44/44.72
MRT1P-7.5/7.62-7P	7	51.5/52.34
MRT1P-7.5/7.62-8P	8	59/59.96
MRT1P-7.5/7.62-9P	9	66.5/67.58
MRT1P-7.5/7.62-10P	10	74/75.2
MRT1P-7.5/7.62-11P	11	81.5/82.82
MRT1P-7.5/7.62-12P	12	89/90.44