



Accessories

Certification	
Material	
Pin/Plate	Copper Alloy, Tin Plated
Housing	PA66, UL94V-O, Green
Electrical	
Standard	UL 1059/CSA, C22.2 No158
Rated Voltage	300 V
Rated Current	15 A
Contact Resistance	20m Ω
Withstand Voltage	1600 Vac/1Min
Mechanical	
Temperature Range	-40°C to +105°C
Size	
Ptich	5.08 mm (.200")
Poles	2P-16P, Additional Sizes available on request

Item	No. Of Poles	Length (mm)
ASIWJ2EDGLM-5.08-2P	2	20.32
ASIWJ2EDGLM-5.08-3P	3	25.41
ASIWJ2EDGLM-5.08-4P	4	30.48
ASIWJ2EDGLM-5.08-5P	5	35.86
ASIWJ2EDGLM-5.08-6P	6	40.64
ASIWJ2EDGLM-5.08-7P	7	45.72
ASIWJ2EDGLM-5.08-8P	8	50.80
ASIWJ2EDGLM-5.08-9P	9	55.88
ASIWJ2EDGLM-5.08-10P	10	90.96
ASIWJ2EDGLM-5.08-11P	11	66.04
ASIWJ2EDGLM-5.08-12P	12	71.12
ASIWJ2EDGLM-5.08-13P	13	76.20
ASIWJ2EDGLM-5.08-14P	14	81.36
ASIWJ2EDGLM-5.08-15P	15	86.36
ASIWJ2EDGLM-5.08-16P	16	91.44