



Certifications	
Material	
Screw	M2.5 Steel Zinc plated
Pin/plate	Copper Alloy, Tin plated
Housing	PA66 UL94V-0, Green
Electrical	
Standard	UL1059/CSA C22.2 No.158
Rated Voltage	300V
Rated Current	15A
Wire range	-
Contact resistance	20m Ω
Insulation resistance	500M Ω /500 Vdc
Withstand Voltage	1600 Vac/1Min
Mechanical	
Temperature range	-40 $^{\circ}$ C~+105 $^{\circ}$ C
Torque	-
Strip length	-
Size	
Pitch	5.08mm(.200")
Poles	2P-16P. Additional sizes available on request

Item	Positions	Length (mm)
ASIWJ2EDGRTM-5.08-2P	2	22.5
ASIWJ2EDGRTM-5.08-3P	3	27.5
ASIWJ2EDGRTM-5.08-4P	4	32.5
ASIWJ2EDGRTM-5.08-5P	5	37.5
ASIWJ2EDGRTM-5.08-6P	6	42.5
ASIWJ2EDGRTM-5.08-7P	7	47.5
ASIWJ2EDGRTM-5.08-8P	8	52.5
ASIWJ2EDGRTM-5.08-9P	9	57.5
ASIWJ2EDGRTM-5.08-10P	10	62.5
ASIWJ2EDGRTM-5.08-11P	11	67.5
ASIWJ2EDGRTM-5.08-12P	12	72.5
ASIWJ2EDGRTM-5.08-13P	13	77.5
ASIWJ2EDGRTM-5.08-14P	14	82.5
ASIWJ2EDGRTM-5.08-15P	15	87.5
ASIWJ2EDGRTM-5.08-16P	16	92.5