


Certification	
	
Material	
Pin	Copper Alloy, Tin Plated
Housing	LCP, UL 94V-0, Black
Electrical	
Standard	UL 1059/CSA C22.2 No. 158
Rated Voltage	300 V
Rated Current	15 A
Contact Resistance	20mΩ
Insulation Resistance	500MΩ/500 Vdc
Withstand Voltage	2000 Vac/1 Min
Mechanical	
Temperature Range	-40°C...+130°C
Size	
Pitch	5.08 mm (.200")
Poles	2P-12P. Additional sizes available on request.

Item	No. of Poles	Length (mm)
ASIWJ2EDGVC-THT-5.08-2P	2	11.56
ASIWJ2EDGVC-THT-5.08-3P	3	16.64
ASIWJ2EDGVC-THT-5.08-4P	4	21.72
ASIWJ2EDGVC-THT-5.08-5P	5	26.8
ASIWJ2EDGVC-THT-5.08-6P	6	31.88
ASIWJ2EDGVC-THT-5.08-7P	7	36.96
ASIWJ2EDGVC-THT-5.08-8P	8	42.04
ASIWJ2EDGVC-THT-5.08-9P	9	50.12
ASIWJ2EDGVC-THT-5.08-10P	10	55.2
ASIWJ2EDGVC-THT-5.08-11P	11	60.28
ASIWJ2EDGVC-THT-5.08-12P	12	65.36