



Certification	
Material	
Locking Nut	M2.5, Copper Alloy
Pin	Copper Alloy, Tin Plated
Housing	LCP, UL 94V-0, Black
Electrical	
Standard	UL 1059/CSA C22.2 No. 158
Rated Voltage	300 V
Rated Current	15 A
Contact Resistance	20mΩ
Insulation Resistance	500MΩ/500 Vdc
Withstand Voltage	2000 Vac/1 Min
Mechanical	
Temperature Range	-40°C...+130°C
Size	
Pitch	5.08 mm (.200")
Poles	2P-12P. Additional sizes available on request.

Item	No. of Poles	Length (mm)
ASIWJ2EDGVM-THT-5.08-2P	2	20.32
ASIWJ2EDGVM-THT-5.08-3P	3	25.4
ASIWJ2EDGVM-THT-5.08-4P	4	30.48
ASIWJ2EDGVM-THT-5.08-5P	5	35.56
ASIWJ2EDGVM-THT-5.08-6P	6	40.64
ASIWJ2EDGVM-THT-5.08-7P	7	45.72
ASIWJ2EDGVM-THT-5.08-8P	8	50.8
ASIWJ2EDGVM-THT-5.08-9P	9	55.88
ASIWJ2EDGVM-THT-5.08-10P	10	60.96
ASIWJ2EDGVM-THT-5.08-11P	11	66.04
ASIWJ2EDGVM-THT-5.08-12P	12	71.12