


Certifications	
	
Material	
Screw	M2.5 Steel Zinc Plated
Pin/Plate	Copper Alloy, Tin Plated
Wire Cage	Copper Alloy, Nickel Plated
Housing	PA 66 UL94V-0, Green
Electrical	
Standard	UL1059/CSA C22.2 No.158
Rated Voltage	300V
Rated Current	16A
Wire Range	30-14AWG
Contact Resistance	20mΩ
insulation Resistance	500MΩ/500Vdc
Withstand Voltage	2000Vac/1Min
Mechanical	
Temperature range	-30°C~+120°C
Torque	0.4Nm (3.5lb-in)
Strip length	6mm
Size	
Pitch	5.0mm
Poles	2P-24P

Item	Positions	Length (mm)
MRT12P5-2VE	2	10
MRT12P5-3VE	3	15
MRT12P5-4VE	4	20
MRT12P5-5VE	5	25
MRT12P5-6VE	6	30
MRT12P5-7VE	7	35
MRT12P5-8VE	8	40
MRT12P5-9VE	9	45
MRT12P5-10VE	10	50
MRT12P5-11VE	11	55
MRT12P5-12VE	12	60
MRT12P5-13VE	13	65
MRT12P5-14VE	14	70
MRT12P5-15VE	15	75
MRT12P5-16VE	16	80
MRT12P5-17VE	17	85
MRT12P5-18VE	18	90
MRT12P5-19VE	19	95
MRT12P5-20VE	20	100
MRT12P5-21VE	21	105
MRT12P5-22VE	22	110
MRT12P5-23VE	23	115
MRT12P5-24VE	24	120