


Certifications	
	
Material	
Screw	M3 Steel Zinc Plated
Pin/Plate	Copper Alloy, Tin Plated
Wire Cage	Copper Alloy, Nickel Plated
Housing	PA 66 UL94V-0, Green
Electrical	
Standard	UL1059/CSA C22.2 No.158
Rated Voltage	300V
Rated Current	14A
Wire Range	30-12AWG
Contact Resistance	20mΩ
insulation Resistance	500MΩ/500Vdc
Withstand Voltage	2000Vac/1Min
Mechanical	
Temperature range	-30°C~+120°C
Torque	0.5Nm (4.4lb-in)
Strip length	6mm
Size	
Pitch	5.0/5.08mm
Poles	2P-24P

Item	Positions	Length (mm)
CLA5/5.08-2SQVE	2	10 / 10.16
CLA5/5.08-3SQVE	3	15 / 15.24
CLA5/5.08-4SQVE	4	20 / 20.32
CLA5/5.08-5SQVE	5	25 / 25.4
CLA5/5.08-6SQVE	6	30 / 30.48
CLA5/5.08-7SQVE	7	35 / 35.56
CLA5/5.08-8SQVE	8	40 / 40.64
CLA5/5.08-9SQVE	9	45 / 45.72
CLA5/5.08-10SQVE	10	50 / 50.8
CLA5/5.08-11SQVE	11	55 / 55.88
CLA5/5.08-12SQVE	12	60 / 60.96
CLA5/5.08-13SQVE	13	65 / 66.04
CLA5/5.08-14SQVE	14	70 / 71.12
CLA5/5.08-15SQVE	15	75 / 76.2
CLA5/5.08-16SQVE	16	80 / 81.28
CLA5/5.08-17SQVE	17	85 / 86.36
CLA5/5.08-18SQVE	18	90 / 91.44
CLA5/5.08-19SQVE	19	95 / 96.52
CLA5/5.08-20SQVE	20	100 / 101.6
CLA5/5.08-21SQVE	21	105 / 106.68
CLA5/5.08-22SQVE	22	110 / 111.76
CLA5/5.08-23SQVE	23	115 / 116.84
CLA5/5.08-24SQVE	24	120 / 121.92