


Certifications	
	
Material	
Screw	M3 Steel Zinc plated
Wire Cage	Copper Alloy, Nickel Plated
Pin/plate	Copper Alloy, , Tin plated
Housing	PA66 UL94V-0, Green
Electrical	
Standard	UL1059/CSA C22.2 No.158
Rated Voltage	300V
Rated Current	16A
Wire range	24-12AWG
Contact resistance	20mΩ
Insulation resistance	500MΩ/500 Vdc
Withstand Voltage	2000 Vac/1Min
Mechanical	
Temperature range	-30°C~+55°C
Torque	5.0 in/lb
Strip length	7mm (0.28")
Size	
Pitch	5.0/5.08mm
Poles	2P-20P

Item	Positions	Length (mm)
CPF5.0/5.08-2FV	2	19.9/20.06
CPF5.0/5.08-3FV	3	24.9/25.14
CPF5.0/5.08-4FV	4	29.9/30.22
CPF5.0/5.08-5FV	5	34.9/35.30
CPF5.0/5.08-6FV	6	39.9/40.38
CPF5.0/5.08-7FV	7	44.9/45.46
CPF5.0/5.08-8FV	8	49.9/50.54
CPF5.0/5.08-9FV	9	54.9/55.62
CPF5.0/5.08-10FV	10	59.9/60.70
CPF5.0/5.08-11FV	11	64.9/65.78
CPF5.0/5.08-12FV	12	69.9/70.86
CPF5.0/5.08-13FV	13	74.9/75.94
CPF5.0/5.08-14FV	14	79.9/81.02
CPF5.0/5.08-15FV	15	84.9/86.10
CPF5.0/5.08-16FV	16	89.9/91.18
CPF5.0/5.08-17FV	17	94.9/96.26
CPF5.0/5.08-18FV	18	99.9/101.34
CPF5.0/5.08-19FV	19	104.9/106.42
CPF5.0/5.08-20FV	20	109.9/111.50