


Certifications	
	
Material	
Screw	M3 Steel Zinc Plated
Pin/Plate	Copper Alloy, Tin Plated
Wire Cage	Copper Alloy, Nickel Plated
Housing	PA 66 UL94V-0, Green
Electrical	
Standard	UL1059/CSA C22.2 No.158
Rated Voltage	300V
Rated Current	16A
Wire Range	30-12AWG
Contact Resistance	20mΩ
insulation Resistance	500MΩ/500Vdc
Withstand Voltage	2000Vac/1Min
Mechanical	
Temperature range	-30°C~+120°C
Torque	0.5Nm (4.4lb-in)
Strip length	6mm
Size	
Pitch	5.0/5.08mm
Poles	2P-24P

Item	Positions	Length (mm)
MRT15-5/5.08-2VE	2	10 / 10.16
MRT15-5/5.08-3VE	3	15 / 15.24
MRT15-5/5.08-4VE	4	20 / 20.32
MRT15-5/5.08-5VE	5	25 / 25.4
MRT15-5/5.08-6VE	6	30 / 30.48
MRT15-5/5.08-7VE	7	35 / 35.56
MRT15-5/5.08-8VE	8	40 / 40.64
MRT15-5/5.08-9VE	9	45 / 45.72
MRT15-5/5.08-10VE	10	50 / 50.8
MRT15-5/5.08-11VE	11	55 / 55.88
MRT15-5/5.08-12VE	12	60 / 60.96
MRT15-5/5.08-13VE	13	65 / 66.04
MRT15-5/5.08-14VE	14	70 / 71.12
MRT15-5/5.08-15VE	15	75 / 76.2
MRT15-5/5.08-16VE	16	80 / 81.28
MRT15-5/5.08-17VE	17	85 / 86.36
MRT15-5/5.08-18VE	18	90 / 91.44
MRT15-5/5.08-19VE	19	95 / 96.52
MRT15-5/5.08-20VE	20	100 / 101.6
MRT15-5/5.08-21VE	21	105 / 106.68
MRT15-5/5.08-22VE	22	110 / 111.76
MRT15-5/5.08-23VE	23	115 / 116.84
MRT15-5/5.08-24VE	24	120 / 121.92