











Terminal block
UBJ2-1.5



Terminal block
UBJ2-2.5



Dimensions				
Width/Thickness/Height	(mm)	41 / 7.2 / 40		41 / 9.2 / 40
Screw thread	(mm)	M3		M4
Tightening torque	(Nm)	0.5-0.7		1.5-1.8
Stripping length	(mm)	8		10
Technical data				
Voltage	(V)	660		660
Current	(A)	17.5		24
Cross section	(mm ²)	1.5		2.5
Connection capacity				
Single-strand conductors	(mm ²)	0.75-1.5		1-2.5
Multi-strand conductors	(mm ²)	0.75-1.5		1-2.5
Terminal block	Type	Order no.	Type	Order no.
	UBJ2-1.5 (Brass screw with round head)	271001	UBJ2-2.5 (Brass screw with round head)	271003
	UBJ2-1.5 (Iron screw with round head)	271002	UBJ2-2.5 (Iron screw with round head)	271004
	UBJ2-1.5 (Brass screw with square head)	271045	UBJ2-2.5 (Brass screw with square head)	271023
	UBJ2-1.5 (Iron screw with square head)	271046	UBJ2-2.5 (Iron screw with square head)	271024
Mounting rail				
Can be installed on the rails both  and 				
	TH35-7.5	102001	TH35-7.5	102001
	TH35-15	102005	TH35-15	102005
	G32-15	102002	G32-15	102002
	G32-18	102003	G32-18	102003
End cover				
For electrical isolation in the end of terminal blocks. 	UBJ2-1.5G	272001	UBJ2-1.5G	272001
Fixed bridge				
For cross connection in the terminal center.  2-pos. 3-pos. 10-pos.	UBJ2-1.5/2L	273001	UBJ2-2.5/2L	273004
	UBJ2-1.5/3L	273002	UBJ2-2.5/3L	273005
	UBJ2-1.5/10L	273003	UBJ2-2.5/10L	273006
Insertion bridge				
For the connection points with conductors, makes level bridge possible.  2-pos. 3-pos.	UBJ2-1.5/2BL	273019	UBJ2-2.5/2BL	273021
	UBJ2-1.5/3BL	273020	UBJ2-2.5/3BL	273022
Marker strip				
Horizontally/Vertically  Blank	BB 7 (Blank)	274001	BB 9 (Blank)	274004
Can be printed 1-600, or the technical data according to your requirements. Horizontally  1 2 3 4 5 6 7	BB 7 (Horizontally)	274002	Center BB 9 (Horizontally)	274005
Vertically 	BB 7 (Vertically)	274003	BB 9 (Vertically)	274006
Covering hood				
For dust-proof encapsulation, makes electrical isolation possible. 	UBJ2-1.5F/10	275001	UBJ2-2.5F/10	275002
Screwdriver 	YB 0.6×3.5	304002	YB 0.6×3.5	304002