





### LED PILOT LIGHT Ø22

DESCRIPTION	POWER SUPPLY	CODE	WEIGHT grammi	MIN. PACK QUANTITY	SIZES
 SINGLE LED INDICATOR X1 — ⊗ — X2	AC/DC 6V <b>1</b>	PLML <b>2</b> L6	15	10	
	AC/DC 12V <b>1</b>	PLML <b>2</b> L12	15	10	
	AC/DC 24V	PLML <b>2</b> L24	15	10	
	AC/DC 48V	PLML <b>2</b> L48	15	10	
	AC/DC 110V	PLML <b>2</b> L110	15	10	
	AC 220V	PLML <b>2</b> L220	15	10	
	AC 380V <b>1</b>	PLML <b>2</b> L380	15	10	

COMPLY WITH RULES		EN60947-5-1 / GB14048.5	DIAGRAM
Operational temperature	°C	-5 +40	<b>RESISTANCE</b> 
Operational umidity		45% ... 90%	
AC rated frequency	Hz	50/60	<b>CAPACITY RESISTANCE</b> 
Rated insulation voltage	1 min V	2500V	
Over voltage category	EN60947.1	III	AC 220 ... 380V
Pollution grade	EN60947.1	3	
Protection degree	EN60529	IP65, IP2X terminals	
Connection:			
Terminal block caliber		A2	
Terminal screw		M3,5	
Flexible and solid conductor section	min/max	n. 1 1/2,5 mm <sup>2</sup> - n. 2 1/2,5 mm <sup>2</sup>	
Rated operational voltage Ue	AC/DC V	6, 12, 24, 48, 110	
	AC V	220 - 380	
Rated operational voltage Ie	mA	≤80 6,12V	
	mA	≤20 24, 48, 110, 220, 380V	
Electrical life	h	≥30.000	
Brightness	cd/m <sup>2</sup>	100	
Mounting	mm	Ø22,5	

**1** On demand execution      **2** Insert lens colour code: ■ ■ ■ ■