


Certifications	
	
Material	
Pin/plate	Copper Alloy, Tin plated
Housing	PA66 UL94V-0, Orange/Gray
Electrical	
Standard	UL1059/CSA C22.2 No.158
Rated Voltage	250V
Rated Current	10A
Wire range	30-16AWG
Contact resistance	20mΩ
Insulation resistance	500MΩ/500 Vdc
Withstand Voltage	2000 Vac/1Min
Mechanical	
Temperature range	-40°C~+105°C
Strip length	7mm
Size	
Pitch	5.0mm /5.08mm
Poles	2P-24P. Additional sizes available on request

Item	Positions	Length (mm) 5.0 / 5.08
MRT1P-5.0/5.08-2P	2	11.5 / 11.66
MRT1P-5.0/5.08-3P	3	16.5 / 16.74
MRT1P-5.0/5.08-4P	4	21.5 / 21.82
MRT1P-5.0/5.08-5P	5	26.5 / 26.9
MRT1P-5.0/5.08-6P	6	31.5 / 31.98
MRT1P-5.0/5.08-7P	7	36.5 / 37.06
MRT1P-5.0/5.08-8P	8	41.5 / 42.14
MRT1P-5.0/5.08-9P	9	46.5 / 47.22
MRT1P-5.0/5.08-10P	10	51.5 / 52.3
MRT1P-5.0/5.08-11P	11	56.5 / 57.38
MRT1P-5.0/5.08-12P	12	61.5 / 62.46
MRT1P-5.0/5.08-13P	13	66.5 / 67.54
MRT1P-5.0/5.08-14P	14	71.5 / 72.62
MRT1P-5.0/5.08-15P	15	76.5 / 77.7
MRT1P-5.0/5.08-16P	16	81.5 / 82.78
MRT1P-5.0/5.08-17P	17	86.5 / 87.86
MRT1P-5.0/5.08-18P	18	91.5 / 92.94
MRT1P-5.0/5.08-19P	19	96.5 / 98.02
MRT1P-5.0/5.08-20P	20	101.5 / 103.1