

Ring Lug Terminal Block ASI391005



The ASI391005 is a NEMA style ring lug terminal block with a UL rating of 50A, 600V. The ring terminal M5 screw size accepts wires terminated directly under the rectangular flat washer or wires equipped with ring, fork or spade lugs. The modular DIN rail mounting of the ASI391005 14.5mm wide NEMA style terminal block allows for assembling any number of circuits together. The center of the barrier strip type NEMA terminal block is designed to accept a snap in label for easy visual circuit identification. Other models of the NEMA style DIN rail mount terminal block include up to 309A, double level, and sliding link disconnect.

	Certifications	
		c Al us
	Specifications	
	Terminal Screw Thread Type	M5
	Terminal Screw Thread Length	12mm
	Torque	19 - 24 Lb-In
	Wire Size (AWG):	#12-8 Sol/Str
	Current Rating:	50A
	Voltage Rating:	600V
	Dimensions (HxWxD):	34x14.5x46mm
	Accessories:	
	Plug-In Jumpers:	
	2 pos	ASI393025
	3 pos	ASI393026
	4 pos	ASI393027
	5 pos	ASI393028
	6 pos	ASI393029
	10 pos	ASI393030
	End Bracket:	ASI392002
	DIN Rail (2 meters)	
	7.5 x 35mm slotted	
	7.5 x 35mm non-slotted	
	15 x 35mm slotted	
	15 x 35mm non-slotted	
	Labels	ASI394006